

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 801	09-01-13	Candidate Number		
Skill Title: SELECTION AND USE OF PORTABLE EXTINGUISHERS					
NFPA Objective:	5.3.16	Minimum to pass	10		
PERFORMANCE:				P	F

	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.			
	2.	Selects correct extinguisher given the size of the fire and the type of fuel burning.			
		<ul style="list-style-type: none"> <li>• Ordinary Combustibles</li> <li>• Flammable Liquids</li> <li>• Flammable Gases</li> <li>• Energized Electrical Equipment</li> <li>• Stovetop greases or kitchen fryers</li> </ul>			
	3.	Carries extinguisher to a safe distance from fire.			
	4.	Pulls pin at top of extinguisher, if equipped, and breaks seal.			
	5.	Stands to the side of the extinguisher and charges by activating the cartridge, if equipped.			
	6.	Tests extinguisher to assure proper agent discharge flow is present.			
	7.	Shuts off electricity to the burning object, if applicable, using a concentrated motion for a clean break while looking away from switch panel.			
	8.	Approaches fire from the upwind and uphill side, if possible.			
	9.	Begins discharging agent from a safe distance.			
	10.	Properly discharges the extinguishing agent based on the fire and fuel burning.			
	11.	Keeps carbon dioxide extinguisher on the ground while discharging agent, if applicable.			
	12.	Sweeps the extinguisher nozzle while discharging agent.			
	13.	Assures that the fire is extinguished.			
	14.	On class B or B/C <u>backs</u> away from the fuel source after fire is extinguished.			

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I/II- 802	09-01-13	Candidate Number	
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS FIRE-NOZZLE FIREFIGHTER/CREW LEADER				
NFPA Objective:	5.3.10, 6.3.2, 6.3.4	Minimum to pass	15	
PERFORMANCE:			P	F

<b>1.</b>	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<b>2.</b>	Sets nozzle for a 30-degree fog pattern with a minimum flow of 95 GPM.				
<b>3.</b>	Slowly opens the nozzle fully, prior to entering the structure, to expel air and test the fog pattern.				
<b>4.</b>	Assures backup resources are available.				
<b>5.</b>	Feels door low to high, using the back of an ungloved or partially ungloved hand, prior to opening.				
<b>6.</b>	Assures that the other two firefighters are ready to enter the structure.				
<b>7.</b>	Stays low when entering structure displaying hostile/low visibility conditions.				
<b>8.</b>	Advances hoseline to fire room while approaching from the unburned side.				
<b>9.</b>	Keeps nozzle closed while advancing to fire unless necessary to operate for protection.				
<b>10.</b>	Upon reaching fire, manages fire stream safely and properly based on the conditions present.				
<b>11.</b>	Calls for first backup firefighter to ventilate structure, calls for second backup to start overhaul.				
<b>12.</b>	Places nozzle outside of the building opening in preparation for hydraulic ventilation.				
<b>13.</b>	Slowly opens the nozzle.				
<b>14.</b>	Retracts the nozzle into the building approximately two (2) feet.				
<b>15.</b>	Adjusts fog pattern to fill approximately the upper 85-90% of the opening with the stream slightly touching the sides of the opening.				
<b>16.</b>	Holds stream steady until smoke has cleared or else is ordered back to the fire origin.				
<b>17.</b>	Stops hydraulic ventilation by advancing the nozzle outside the building opening.				
<b>18.</b>	Slowly closes the nozzle.				
<b>19.</b>	Assures fire is overhauled and extinguished.				
<b>20.</b>	Communicates fire conditions and crew integrity to Command.				
<b>21.</b>	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 803	09-01-13	Candidate Number		
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS FIRE FIRST BACKUP					
NFPA Objective:	5.3.10, 6.3.4	Minimum to pass	10		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<input checked="" type="checkbox"/>	3.	Carries a forcible entry tool.				
<input checked="" type="checkbox"/>	4.	Stays low when entering structure displaying hostile/low visibility conditions				
<input type="checkbox"/>	5.	Remains behind nozzle firefighter far enough to advance hose to him/her.				
<input type="checkbox"/>	6.	Removes kinks in hoseline during advancement.				
<input type="checkbox"/>	7.	Keeps hoseline opposite protruding corners to avoid kinking.				
<input type="checkbox"/>	8.	Advances hoseline based on the need of the nozzle firefighter.				
<input type="checkbox"/>	9.	Joins the nozzle firefighter after the hoseline is in position.				
<input type="checkbox"/>	10.	Upon order from nozzle firefighter ventilates structure.				
<input type="checkbox"/>	11.	Assists with overhaul of burning materials with a tool, not the hands.				
<input type="checkbox"/>	12.	Orders nozzle firefighter back to origin to wet burning materials if necessary.				
<input checked="" type="checkbox"/>	13.	Assures fire is overhauled and extinguished.				
<input checked="" type="checkbox"/>	14.	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 804	09-01-13	Candidate Number		
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS FIRE- SECOND BACKUP					
NFPA Objective:	5.3.10, 6.3.4	Minimum to pass	9		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<input checked="" type="checkbox"/>	3.	Takes a forcible entry tool.				
<input type="checkbox"/>	4.	Stays low when entering structure displaying hostile/low visibility conditions.				
<input type="checkbox"/>	5.	Remains outside of doorways while advancing hoseline.				
<input type="checkbox"/>	6.	Removes kinks in hoseline during advancement.				
<input type="checkbox"/>	7.	Keeps hoseline opposite protruding corners to avoid kinking.				
<input type="checkbox"/>	8.	Advances hoseline based on the need of the nozzle firefighter.				
<input type="checkbox"/>	9.	Remains back away from the first backup firefighter in preparation to advance more hose.				
<input checked="" type="checkbox"/>	10.	Moves up to fire area if called by the nozzle, the first backup firefighter, or once extra hose is no longer needed.				
<input type="checkbox"/>	11.	Overhauls burning materials when ordered by nozzle firefighter.				
<input type="checkbox"/>	12.	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I/II- 805	09-01-13	Candidate Number		
Skill Title: EXTINGUISH A VEHICLE FIRE-NOZZLE FIREFIGHTER/CREW LEADER					
NFPA Objective:	5.3.7, 6.3.2	Minimum to pass	11		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Sets nozzle for a straight stream pattern with a minimum flow of 95 GPM.				
<input checked="" type="checkbox"/>	3.	Slowly opens the nozzle fully, prior to approaching vehicle, to expel air and test the stream pattern.				
<input type="checkbox"/>	4.	Assures other two firefighters are ready to approach.				
<input type="checkbox"/>	5.	Advances from uphill, upwind, and from the side of the vehicle if possible.				
<input type="checkbox"/>	6.	Advances closed hoseline to approximately 100 feet from vehicle.				
<input checked="" type="checkbox"/>	7.	Slowly opens the nozzle.				
<input checked="" type="checkbox"/>	8.	Properly and safely manages fire stream to cool vehicle hazard area. (Fuel tanks, engine compartment through radiator, tires, split rims, bumpers, air suspension systems, drive shafts, etc.)				
<input type="checkbox"/>	9.	Extinguishes surrounding fires, if present.				
<input type="checkbox"/>	10.	Cools exposures, if present.				
<input type="checkbox"/>	11.	Increases fog pattern size as distance to vehicle is reduced.				
<input type="checkbox"/>	12.	Orders first backup firefighter to open vehicle compartments. (Door, hood, and trunk)				
<input type="checkbox"/>	13.	Extinguishes fire as exposed.				
<input checked="" type="checkbox"/>	14.	Communicates fire conditions and crew integrity to Command.				
<input checked="" type="checkbox"/>	15.	Assures fire is overhauled and extinguished.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 806	09-01-13	Candidate Number		
Skill Title: EXTINGUISH A VEHICLE FIRE-FIRST BACKUP					
NFPA Objective:	5.3.7	Minimum to pass	7		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	3.	Carries a forcible entry tool.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	4.	Advances hoseline based on the need of the nozzle firefighter.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	5.	Removes kinks in hoseline during advancement.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	6.	Joins the nozzle firefighter once the hoseline is in position.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	7.	Upon order from nozzle firefighter, opens vehicle compartments. (Doors, hood, and trunk)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	8.	Overhauls burning materials with the tool.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	9.	Orders nozzle firefighter back to wet burning materials, if necessary.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	10.	Assures fire is overhauled and extinguished.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 807	09-01-13	Candidate Number		
Skill Title: EXTINGUISH A VEHICLE FIRE-SECOND BACKUP					
NFPA Objective:	5.3.7	Minimum to pass	7		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<input type="checkbox"/>	3.	Advances hoseline based on the need of the first backup firefighter.				
<input type="checkbox"/>	4.	Removes kinks in hoseline during advancement.				
<input type="checkbox"/>	5.	Remains back away from the first backup firefighter in preparation to advance more hose.				
<input type="checkbox"/>	6.	Moves up to origin if called by the nozzle, first backup firefighter, or once the need for more hose ceases.				
<input type="checkbox"/>	7.	If safe, properly disconnects battery from vehicle. (Negative side first.)				
<input checked="" type="checkbox"/>	8.	Assists first backup firefighter with opening vehicle compartments. (Doors, Hood and trunk)				
<input type="checkbox"/>	9.	Assists with overhauling burning materials.				
<input checked="" type="checkbox"/>	10.	Assures fire is overhauled and extinguished.				

<input checked="" type="checkbox"/>	Failure of this critical portion is cause for entire skill failure
Examiner Name: _____	Signature: _____ Date: ___/___/___
Please circle:	<input type="radio"/> PASS <input type="radio"/> FAIL <input type="radio"/> RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I/II- 808	09-01-13	Candidate Number		
Skill Title: EXTINGUISH A DUMPSTER FIRE-NOZZLE FIREFIGHTER/CREW LEADER					
NFPA Objective:	5.3.8, 6.3.2	Minimum to pass	11		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Sets nozzle for a straight stream pattern with a minimum flow of 95 GPM.				
<input checked="" type="checkbox"/>	3.	Slowly opens the nozzle fully, prior to approaching dumpster, to expel air and test the stream pattern.				
<input type="checkbox"/>	4.	Assures that the other two firefighters are ready to approach.				
<input type="checkbox"/>	5.	Advances from uphill and upwind, if possible.				
<input type="checkbox"/>	6.	Advances closed hoseline to approximately 100 feet from dumpster.				
<input checked="" type="checkbox"/>	7.	Slowly opens the nozzle.				
<input checked="" type="checkbox"/>	8.	Properly and safely manages fire stream to cool the dumpster and surrounding exposures.				
<input type="checkbox"/>	9.	Extinguishes surrounding fires, if present.				
<input type="checkbox"/>	10.	Orders first backup firefighter to open dumpster openings. (Top or sides)				
<input type="checkbox"/>	11.	Extinguishes fire as exposed.				
<input type="checkbox"/>	12.	Hydraulically overhauls material as much as possible limiting personnel exposure.				
<input type="checkbox"/>	13.	Does not use excessive pressure during overhaul to avoid blowing and splattering material on personnel.				
<input checked="" type="checkbox"/>	14.	Communicates fire conditions and crew integrity to Command.				
<input checked="" type="checkbox"/>	15.	Assures fire is overhauled and extinguished.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 809	09-01-13	Candidate Number		
Skill Title: EXTINGUISH A DUMPSTER FIRE-FIRST BACKUP					
NFPA Objective:	5.3.8	Minimum to pass	7		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	3.	Carries a forcible entry tool.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	4.	Advances hoseline based on the need of the nozzle firefighter.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	5.	Removes kinks in hoseline during advancement.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	6.	Joins the nozzle firefighter once the hoseline is in position.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	7.	Upon order from nozzle firefighter, opens dumpster openings with a tool. (Top or side)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	8.	Hydraulic overhaul is preferred, but overhauls burning material with tool, if necessary, limiting exposure to personnel.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	9.	Orders nozzle firefighter back to wet burning materials.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	10.	Assures fire is overhauled and extinguished.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 810	09-01-13	Candidate Number		
Skill Title: EXTINGUISH A DUMPSTER FIRE-SECOND BACKUP					
NFPA Objective:	5.3.8	Minimum to pass	7		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Carries a forcible tool				
<input type="checkbox"/>	3.	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<input type="checkbox"/>	4.	Advances hoseline based on the need of the first backup firefighter.				
<input type="checkbox"/>	5.	Removes kinks in hoseline during advancement.				
<input type="checkbox"/>	6.	Remains back away from the first backup firefighter in preparation to advance more hose.				
<input checked="" type="checkbox"/>	7.	Moves up to origin if called by the nozzle firefighter, first backup firefighter, or once the need for more hose ceases.				
<input type="checkbox"/>	8.	Assists first backup firefighter with opening dumpster openings with tool. (Top or sides)				
<input type="checkbox"/>	9.	Hydraulic overhaul is preferred, but overhauls burning material with tool, if necessary, limiting exposure to personnel.				
<input checked="" type="checkbox"/>	10.	Assures that overhaul is complete and fire is extinguished.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I/II- 811	09-01-13	Candidate Number		
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS ABOVE GRADE FIRE - NOZZLE FIREFIGHTER/CREW LEADER					
NFPA Objective:	5.3.10, 6.3.2	Minimum to pass	16		
PERFORMANCE:				P	F

<b>1.</b>	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<b>2.</b>	Sets nozzle for a 30-degree fog pattern with a minimum flow of 95 GPM.				
<b>3.</b>	Slowly opens the nozzle fully, prior to entering the structure, to expel air and test the fog pattern.				
<b>4.</b>	Assures backup resources are available.				
<b>5.</b>	Feels door low to high, using the back of an ungloved or partially ungloved hand, prior to opening.				
<b>6.</b>	Assures the other two firefighters are ready to enter the structure.				
<b>7.</b>	Stays low when entering structure displaying hostile/low visibility conditions.				
<b>8.</b>	Advances hoseline to fire room while approaching from the unburned side.				
<b>9.</b>	Avoids staying in stairwells.				
<b>10.</b>	Keeps nozzle closed while advancing to fire unless necessary to operate for protection.				
<b>11.</b>	Upon reaching fire, manages fire stream safely and properly based on the conditions present.				
<b>12.</b>	Calls for first backup firefighter to ventilate structure, calls for second backup to start overhaul.				
<b>13.</b>	Places nozzle outside of the building opening in preparation for hydraulic ventilation.				
<b>14.</b>	Slowly opens the nozzle.				
<b>15.</b>	Retracts the nozzle into the building approximately two (2) feet.				
<b>16.</b>	Adjusts fog pattern to fill approximately the upper 85-90% of the opening with the stream slightly touching the sides of the opening.				
<b>17.</b>	Holds stream steady until smoke has cleared or else is ordered back to the fire origin.				
<b>18.</b>	Stops hydraulic ventilation by advancing the nozzle outside the building opening.				
<b>19.</b>	Slowly closes the nozzle.				
<b>20.</b>	Assures fire is overhauled and extinguished.				
<b>21.</b>	Communicates fire conditions and crew integrity to Command.				
<b>22.</b>	Completes evolution using safe fire suppression skills.				

**■ Failure of this critical portion is cause for entire skill failure**

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 812	09-01-13	Candidate Number		
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS ABOVE GRADE FIRE - FIRST BACKUP					
NFPA Objective:	5.3.10	Minimum to pass	11		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<input checked="" type="checkbox"/>	3.	Carries a forcible entry tool.				
<input checked="" type="checkbox"/>	4.	Stays low when entering structure displaying hostile/low visibility conditions				
<input type="checkbox"/>	5.	Remains behind nozzle firefighter far enough to advance hose to him/her.				
<input type="checkbox"/>	6.	Removes kinks in hoseline during advancement.				
<input type="checkbox"/>	7.	Keeps hoseline opposite protruding corners to avoid kinking.				
<input type="checkbox"/>	8.	Advances hoseline based on the need of the nozzle firefighter.				
<input type="checkbox"/>	9.	Joins the nozzle firefighter after the hoseline is in position.				
<input type="checkbox"/>	10.	Upon order from nozzle firefighter ventilates structure.				
<input type="checkbox"/>	11.	Assists with overhaul of burning materials with a tool, not the hands.				
<input type="checkbox"/>	12.	Orders nozzle firefighter back to origin to wet burning materials if necessary.				
<input checked="" type="checkbox"/>	13.	Assures fire is overhauled and extinguished.				
<input checked="" type="checkbox"/>	14.	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 813	09-01-13	Candidate Number		
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS ABOVE GRADE FIRE - SECOND BACKUP					
NFPA Objective:	5.3.10	Minimum to pass	9		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<input checked="" type="checkbox"/>	3.	Takes a forcible entry tool.				
<input type="checkbox"/>	4.	Stays low when entering structure displaying hostile/low visibility conditions.				
<input type="checkbox"/>	5.	Remains outside of doorways while advancing hoseline.				
<input type="checkbox"/>	6.	Removes kinks in hoseline during advancement.				
<input type="checkbox"/>	7.	Keeps hoseline opposite protruding corners to avoid kinking.				
<input type="checkbox"/>	8.	Advances hoseline based on the need of the nozzle firefighter.				
<input type="checkbox"/>	9.	Remains back away from the first backup firefighter in preparation to advance more hose.				
<input checked="" type="checkbox"/>	10.	Moves up to fire area if called by the nozzle, the first backup firefighter, or once extra hose is no longer needed.				
<input type="checkbox"/>	11.	Overhauls burning materials when ordered by nozzle firefighter.				
<input type="checkbox"/>	12.	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I/II- 814	09-01-13	Candidate Number	
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS BELOW GRADE FIRE-NOZZLE FIREFIGHTER/CREW LEADER				
NFPA Objective:	5.3.10, 6.3.2	Minimum to pass	17	
PERFORMANCE:			P	F

<b>1.</b>	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<b>2.</b>	Sets nozzle for a straight stream with a minimum flow of 95 GPM.				
<b>3.</b>	Slowly opens the nozzle fully, prior to entering the structure, to expel air and test the fog pattern.				
<b>4.</b>	Assures backup resources are available.				
<b>5.</b>	Feels door low to high, using the back of an ungloved or partially ungloved hand, prior to opening.				
<b>6.</b>	Assures the other two firefighters are ready to enter the structure.				
<b>7.</b>	Opens door slowly & allows trapped heat & smoke to vent the area.				
<b>8.</b>	Stays low when entering structure w/ hostile/low visibility conditions.				
<b>9.</b>	Keeps hose line in the outer half of the stairway.				
<b>10.</b>	With hose line and while staying low, descends stairwell as quickly as possible to get underneath thermal layer.				
<b>11.</b>	Keeps nozzle closed while advancing to fire unless necessary to operate for protection.				
<b>12.</b>	Upon reaching the fire, manages fire stream safely and properly based on the conditions present.				
<b>13.</b>	Calls for first backup firefighter to open the structure for ventilation, if possible.				
<b>14.</b>	Places nozzle outside of the building in preparation to ventilate hydraulically.				
<b>15.</b>	Slowly opens the nozzle.				
<b>16.</b>	Retracts the nozzle into the building approximately two (2) feet.				
<b>17.</b>	Adjusts fog pattern to fill approximately 85-90% of the opening with the stream slightly touching the sides of the opening.				
<b>18.</b>	Holds stream steady until smoke has cleared or ordered back to the fire origin.				
<b>19.</b>	Stops hydraulic ventilation by advancing the nozzle outside the building opening.				
<b>20.</b>	Slowly closes the nozzle.				
<b>21.</b>	Assures fire is overhauled and extinguished.				
<b>22.</b>	Communicates fire conditions and crew integrity to Command.				
<b>23.</b>	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 815	09-01-13	Candidate Number		
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS BELOW GRADE FIRE-FIRST BACKUP					
NFPA Objective:	5.3.10	Minimum to pass	10		
PERFORMANCE:				P	F

<input checked="" type="checkbox"/>	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<input type="checkbox"/>	2.	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<input checked="" type="checkbox"/>	3.	Carries a forcible entry tool.				
<input checked="" type="checkbox"/>	4.	Stays low when entering structure displaying hostile/low visibility conditions				
<input type="checkbox"/>	5.	Keeps hose line in the outer half of the stairway.				
<input type="checkbox"/>	6.	Removes kinks in hose line during advancement.				
<input type="checkbox"/>	7.	Keeps hose line opposite protruding corners to avoid kinking.				
<input type="checkbox"/>	8.	Advances hose line based on the need of the nozzle firefighter as quickly as possible to get underneath thermal layer.				
<input type="checkbox"/>	9.	Joins the nozzle firefighter once the hose line is in position.				
<input type="checkbox"/>	10.	Upon order from nozzle firefighter, opens structure for ventilation, if possible.				
<input type="checkbox"/>	11.	Overhauls burning materials with the tool, not hands.				
<input type="checkbox"/>	12.	Orders nozzle firefighter back to origin to wet burning materials, if necessary.				
<input checked="" type="checkbox"/>	13.	Assures fire is overhauled and extinguished.				
<input checked="" type="checkbox"/>	14.	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-I- 816	09-01-13	Candidate Number		
Skill Title: EXTINGUISH AN INTERIOR CLASS "A" MATERIALS BELOW GRADE FIRE-SECOND BACKUP					
NFPA Objective:	5.3.10	Minimum to pass		9	
PERFORMANCE:				P	F

<b>1.</b>	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<b>2.</b>	Takes a position on the same side of the hoseline relative to nozzle firefighter.				
<b>3.</b>	Carries a forcible entry tool.				
<b>4.</b>	Stays low when entering structure displaying hostile/low visibility conditions.				
<b>5.</b>	Keeps hose line in the outer half of the stairway.				
<b>6.</b>	Removes kinks in hose line during advancement.				
<b>7.</b>	Keeps hose line opposite protruding corners to avoid kinking.				
<b>8.</b>	Advances hose line based on the need of the first backup firefighter.				
<b>9.</b>	Remains back away from the first backup firefighter in preparation to advance more hose.				
<b>10.</b>	Moves up to origin if called by the nozzle firefighter, first backup firefighter, or as the need for more hose ceases.				
<b>11.</b>	Assures that burning material is overhauled and fire is extinguished.				
<b>12.</b>	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-II- 901	09-01-13	Candidate Number	
Skill Title: EXTINGUISH AN EXTERIOR FLAMMABLE LIQUID FIRE WITH FOAM WHILE USING SCBA				
NFPA Objective:	6.3.1	Minimum to pass		11
PERFORMANCE:				P      F

	1.	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
	2.	Assures the foam nozzle, the in-line eductor, and the foam concentrate are both GPM and percentage of concentrate compatible.				
	3.	Stretches and connects sufficient hose from the engine discharge to the point of the foam eduction operation, as determined by the examiner.				
	4.	Connects the in-line eductor to the hoseline.				
	5.	Connects the proper foam nozzle to a sufficient length of hoseline to reach the intended target from the eduction point.				
	6.	Places the supply of foam concentrate near the in-line eductor.				
	7.	Places the in-line eductor pick-up tube into the foam concentrate container.				
	8.	Indicates to the pump operator to charge hoseline.				
	9.	At this point goes on positive pressure air supply, activates PASS device.				
	10.	Removes kinks in hoseline during advancement.				
	11.	Turns the foam nozzle away from the fire, slowly opens the foam nozzle and assures proper foam stream is being generated.				
	12.	Applies foam in either a finished foam spray or indirectly by directing the stream against a stationary object allowing the foam to spread over the burning fuel with as little agitation as possible.				
	13.	If foam stops while in the process of application, the firefighter redirects the stream away from the existing foam blanket.				
	14.	Extinguishes the fire using foam.				
	15.	Backs away from the fuel source after fire is extinguished.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle:                                      **PASS**                                      **FAIL**                                      **RETAKE**

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-II- 911	09-01-13	Candidate Number		
Skill Title:	CONTROL AN EXTERIOR FLAMMABLE GAS FIRE FROM A 20 LB. CYLINDER WITH A HOSELINE WHILE USING SCBA– NOZZLE POSITION/CREW LEADER				
NFPA Objective:	6.3.3, 6.3.2	Minimum to pass	11		
PERFORMANCE:				P	F

<b>1.</b>	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<b>2.</b>	Sets nozzle for a 30-degree fog pattern with a minimum flow of 100 GPM.				
<b>3.</b>	Slowly opens the nozzle <u>fully</u> , to expel air and test the fog pattern.				
<b>4.</b>	Hoseline selected is of sufficient length to encircle the fire area if wind direction changes.				
<b>5.</b>	Assures that the other two firefighters are ready to enter the fire area.				
<b>6.</b>	Advances hose line to fire approaching from the upwind side				
<b>7.</b>	Keeps nozzle <i>open fully</i> while advancing on fire, widening the fog pattern as needed for protection.				
<b>8.</b>	Upon reaching the fire, assures the fog-stream is positioned to push vapors/fire away from cylinder and valve to be closed without reaching through the fog stream.				
<b>9.</b>	Calls for second backup firefighter to stabilize cylinder with rake or hook.				
<b>10.</b>	Calls for first backup firefighter to close the cylinder valve.				
<b>11.</b>	Assures fire is extinguished after stopping the flow of the gas.				
<b>12.</b>	Maintains fog-stream, backing the line away from the fuel source while avoiding kinks.				
<b>13.</b>	Remains standing, not kneeling, throughout evolution.				
<b>14.</b>	Communicates fire conditions and crew integrity to Command.				
<b>15.</b>	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-II- 912	09-01-13	Candidate Number		
Skill Title:	CONTROL AN EXTERIOR FLAMMABLE GAS FIRE FROM A 20 LB. CYLINDER WITH A HOSELINE WHILE USING SCBA- FIRST BACK-UP POSITION.				
NFPA Objective:	6.3.3	Minimum to pass	11		
PERFORMANCE:				P	F

<b>1.</b>	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<b>2.</b>	Takes position on the same side of the hoseline as the nozzle firefighter.				
<b>3.</b>	Removes kinks in the hoseline prior to advancing the line.				
<b>4.</b>	Checks for any obstacles in the area during the fire attack to maintain the safety of the fog pattern.				
<b>5.</b>	Assures the line is of sufficient length in order to encircle the fire area if wind direction changes.				
<b>6.</b>	Keeps the hoseline straight while approaching from the upwind side				
<b>7.</b>	Assures the line is without kinks while advancing on the fire.				
<b>8.</b>	Upon reaching the fire, closes cylinder valve to stop gas flow.				
<b>9.</b>	Does not reach through hose stream at any time.				
<b>10.</b>	Advises the nozzle firefighter status of cylinder valve and returns to the hoseline to assist with retreat.				
<b>11.</b>	Coordinates with second back-up person, in order that the fire crew does not trip over the retreating hoseline while backing out.				
<b>12.</b>	Maintains the proper stream, backing the line away from the fuel source, while avoiding kinks.				
<b>13.</b>	Remains standing, not kneeling, throughout evolution.				
<b>14.</b>	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE

# Massachusetts Fire Training Council Firefighter Practical Certification Examination

Skill Sheet No.	FF-II-913	09-01-13	Candidate Number	
Skill Title: CONTROL AN EXTERIOR FLAMMABLE GAS FIRE FROM A 20 LB. CYLINDER WITH A HOSELINE WHILE USING SCBA- SECOND BACK-UP POSITION.				
NFPA Objective:	6.3.3	Minimum to pass	6	
PERFORMANCE:			P	F

<b>1.</b>	Wears full protective clothing, utilizes positive pressure SCBA, and PASS device on.				
<b>2.</b>	Takes a position on the same side of the hoseline relative to nozzle firefighter with a rake or hook.				
<b>3.</b>	Removes kinks in the hoseline prior to advancing.				
<b>4.</b>	Advances hose line based on the need of the first backup firefighter.				
<b>5.</b>	Once nozzle is in position to protect the cylinder valve, comes off hoseline to stabilize cylinder with rake or hook.				
<b>6.</b>	Returns to hoseline to assist with retreat.				
<b>7.</b>	Remains standing, not kneeling, throughout evolution.				
<b>8.</b>	Completes evolution using safe fire suppression skills.				

Failure of this critical portion is cause for entire skill failure

Examiner Name: \_\_\_\_\_ Signature: \_\_\_\_\_ Date: \_\_\_/\_\_\_/\_\_\_

Please circle: PASS FAIL RETAKE