

310 CMR: DEPARTMENT OF ENVIRONMENTAL PROTECTION

310 CMR 6.00: AMBIENT AIR QUALITY STANDARDS FOR THE COMMONWEALTH OF MASSACHUSETTS

Section

6.01: Definitions

6.02: Scope

6.03: Reference Conditions

6.04: Standards

6.01: Definitions

Ambient Air means that portion of the atmosphere, external to buildings, to which the general public has access.

Department means the Department of Environmental Protection.

Equivalent method means ~~any~~ method of sampling and analyzing the ambient air for an air pollutant ~~which can be demonstrated to the Department's satisfaction to have a consistent relationship to the reference method that has been designated as an equivalent method in accordance with 40 CFR Part 53; it does not include a method for which an equivalent method designation has been canceled in accordance with 40 CFR Part 53.11 or 53.16.~~

Reference method means a method of sampling and analyzing the ambient air for an air pollutant, ~~as described in the Federal Register, Volume 36, number 228, November 25, 1971 that is specified as a reference method in an appendix to 40 CFR Part 50, or a method that has been designated as a reference method in accordance with 40 CFR Part 53; it does not include a method for which a reference method designation has been cancelled in accordance with 40 CFR Part 53.11 or 53.16.~~

6.02: Scope.

(1) Primary ambient air quality standards define levels of air quality which the Department judges are necessary, with an adequate margin of safety, to protect the public health. Secondary ambient air quality standards define levels of air quality which the Department judges are necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant. Such standards are subject to revision, and additional primary and secondary standards may be promulgated as the Department deems necessary to protect the public health and welfare.

(2) The promulgation of primary and secondary ambient air quality standards shall not be considered in any manner to allow significant deterioration of existing air quality in any portion of the Commonwealth.

6.03: Reference Conditions

~~All measurements of air quality are corrected to a reference temperature of 25°C and to a reference pressure of 760 millimeters of mercury (1,013.2 millibars). All measurements of air quality that are expressed as mass per unit volume (e.g., micrograms per cubic meter) other than for particulate matter (PM_{2.5}) standards contained in 310 CMR 6.04(2)(b) and (c), and lead standards contained in 310 CMR 6.04(6), shall be corrected to a reference temperature of 25 (deg) C and a reference pressure of 760 millimeters of mercury (1,013.2 millibars). Measurements of PM_{2.5} for purposes of comparison to the standards contained in 310 CMR 6.04(2)(b) and (c), and of lead for purposes of comparison to the standards contained in 310 CMR 6.04(6) shall be reported based on actual ambient air volume measured at the actual ambient temperature and pressure at the monitoring site during the measurement period.~~

6.04: Standards

(1) ~~Oxides of Sulfur-Oxides~~ (sulfur dioxide).

(a) ~~Primary Ambient Air Quality Standards for Oxides of Sulfur-Oxides~~ (sulfur dioxide): ~~The primary ambient air quality standards for sulfur oxides, measured as sulfur dioxide by the reference method described in 40 CFR Part 50 or by an equivalent method, are:~~

- ~~1. 80 micrograms per cubic meter (0.03 p.p.m.) annual arithmetic mean.~~
- ~~2. 365 micrograms per cubic meter (0.14 p.p.m.) Maximum 24 hour concentration not to be exceeded more than once per year.~~

1. The level of the primary 1-hour ambient air quality standard for oxides of sulfur is 75 parts per billion (ppb, which is 1 part in 1,000,000,000), measured in the ambient air as sulfur dioxide (SO₂).

2. The 1-hour primary standard is met at an ambient air quality monitoring site when the three-year average of the annual (99th percentile) of the daily maximum 1-hour average concentrations is less than or equal to 75 ppb, as determined in accordance with appendix T of 40 CFR Part 50.

3. The level of the standard shall be measured by a reference method based on appendix A or A-1 of 40 CFR Part 50, or by a federal equivalent method (FEM) designated in accordance with 40 CFR Part 53.

(b) ~~Secondary Ambient Air Quality Standards for Oxides of Sulfur-Oxides~~ (sulfur dioxide): ~~The national secondary ambient air quality standard for sulfur oxides, measured as sulfur dioxide by the reference method described in 40 CFR Part 50 is: 1,300 micrograms per cubic meter (0.5 p.p.m.) maximum three hour concentration not to be exceeded more than once per year.~~

1. The level of the secondary 3-hour ambient air quality standard for oxides of sulfur is 0.5 parts per million (ppm), not to be exceeded more than once per calendar year. The 3-hour averages shall be determined from

successive non-overlapping 3-hour blocks starting at midnight each calendar day and shall be rounded to 1 decimal place (fractional parts equal to or greater than 0.05 ppm shall be rounded up).

2. Oxides of sulfur shall be measured in the ambient air as sulfur dioxide by the reference method described in appendix A of 40 CFR Part 50 or by a federal equivalent method designated in accordance with 40 CFR Part 53.

3. To demonstrate attainment, the second-highest 3-hour average must be based upon hourly data that are at least 75 percent complete in each calendar quarter. A 3-hour block average shall be considered valid only if all three hourly averages for the 3-hour period are available. If only one or two hourly averages are available, but the 3-hour average would exceed the level of the standard when zeros are substituted for the missing values, subject to the rounding rule of paragraph (1.) of this section, then this shall be considered a valid 3-hour average. In all cases, the 3-hour block average shall be computed as the sum of the hourly averages divided by 3.

(2) Particulate Matter.

(a) ~~Primary and Secondary Ambient Air Quality Standards for PM₁₀:~~Particulate Matter. The primary ambient air quality standards for particulate matter, measured by the reference method described in Appendix J of 40 CFR Part 50, or by an equivalent method, are:

1. ~~50 micrograms per cubic meter annual ambient air quality standard, attained when the expected annual mean arithmetic concentration, as determined in accordance with Appendix K to 40 CFR Part 50, is less than or equal to 50 micrograms per cubic meter.~~

2. ~~150 micrograms per cubic meter maximum 24-hour concentration, attained when the expected number of days per calendar year with a 24-hour average concentration above 150 micrograms per cubic meter, as determined in accordance with Appendix K to 40 CFR Part 50, is less than or equal to one.~~

3. ~~For purposes of determining attainment with standards, particulate matter shall be measured in the ambient air as PM₁₀.~~

1. The level of the primary and secondary 24-hour ambient air quality standards for particulate matter is 150 micrograms per cubic meter ($\mu\text{g}/\text{m}^3$), 24-hour average concentration. The standards are attained when the expected number of days per calendar year with a 24-hour average concentration above 150 $\mu\text{g}/\text{m}^3$, as determined in accordance with appendix K to 40 CFR Part 50, is equal to or less than one.

2. For the purpose of determining attainment of the primary and secondary standards, particulate matter shall be measured in the ambient air as PM₁₀ (particles with an aerodynamic diameter less than or equal to a nominal 10 micrometers) by:

a. A reference method based on appendix J of 40 CFR Part 50 and designated in accordance with 40 CFR Part 53, or

b. An equivalent method designated in accordance with 40 CFR Part 53.

(b) Primary Ambient Air Quality Standards for PM_{2.5}:

1. The primary ambient air quality standards for PM_{2.5} are 12.0 micrograms per cubic meter ($\mu\text{g}/\text{m}^3$) annual arithmetic mean concentration and 35 $\mu\text{g}/\text{m}^3$ 24-hour average concentration measured in the ambient air as PM_{2.5} (particles with an aerodynamic diameter less than or equal to a nominal 2.5 micrometers) by either:

a. A reference method based on appendix L to 40 CFR Part 50 and designated in accordance with 40 CFR Part 53; or

b. An equivalent method designated in accordance with 40 CFR Part 53.

2. The primary annual PM_{2.5} standard is met when the annual arithmetic mean concentration, as determined in accordance with appendix N of 40 CFR Part 50, is less than or equal to 12.0 $\mu\text{g}/\text{m}^3$.

3. The primary 24-hour PM_{2.5} standard is met when the 98th percentile 24-hour concentration, as determined in accordance with appendix N of 40 CFR Part 50, is less than or equal to 35 $\mu\text{g}/\text{m}^3$.

(c) ~~Secondary Ambient Air Quality Standards for PM_{2.5}:Particulate Matter. Identical to those of the Primary Ambient Air Quality Standards for Particulate Matter.~~

1. The secondary ambient air quality standards for ~~particulate matter~~PM_{2.5} are 15.0 micrograms per cubic meter ($\mu\text{g}/\text{m}^3$) annual arithmetic mean concentration, and 35 $\mu\text{g}/\text{m}^3$ 24-hour average concentration measured in the ambient air as PM_{2.5} (particles with an aerodynamic diameter less than or equal to a nominal 2.5 micrometers) by either:

a. A reference method based on appendix L of 40 CFR Part 50 and designated in accordance with 40 CFR Part 53; or

b. An equivalent method designated in accordance with 40 CFR Part 53.

2. The annual secondary PM_{2.5} standard is met when the annual arithmetic mean concentration, as determined in accordance with appendix N of 40 CFR Part 50, is less than or equal to 15.0 $\mu\text{g}/\text{m}^3$.

3. The 24-hour secondary PM_{2.5} standard is met when the 98th percentile 24-hour concentration, as determined in accordance with appendix N of 40 CFR Part 50, is less than or equal to 35 µg/m³.

(3) ~~Primary and Secondary Ambient Air Quality Standards for Carbon Monoxide.~~ The primary and secondary ambient air quality standards for carbon monoxide, measured by the reference method described in 40 CFR Part 50, or by an equivalent method, are:

(a) The primary ambient air quality standards for carbon monoxide are: 40 milligrams per cubic meter (9 p.p.m.) — maximum 8-hour concentration not to be exceeded more than once per year.

(b) ~~40 milligrams per cubic meter (35 p.p.m.) — maximum 1-hour concentration not to be exceeded more than once per year.~~

1. 9 parts per million (10 milligrams per cubic meter) for an 8-hour average concentration not to be exceeded more than once per year, and

2. 35 parts per million (40 milligrams per cubic meter) for a 1-hour average concentration not to be exceeded more than once per year.

(b) The levels of carbon monoxide in the ambient air shall be measured by:

1. A reference method based on appendix C of 40 CFR Part 50 and designated in accordance with 40 CFR Part 53, or

2. An equivalent method designated in accordance with 40 CFR Part 53.

(c) An 8-hour average shall be considered valid if at least 75 percent of the hourly average for the 8-hour period are available. In the event that only six (or seven) hourly averages are available, the 8-hour average shall be computed on the basis of the hours available using six (or seven) as the divisor.

(d) When summarizing data for comparison with the standards, averages shall be stated to one decimal place. Comparison of the data with the levels of the standards in parts per million shall be made in terms of integers with fractional parts of 0.5 or greater rounding up.

(4) ~~Primary and Secondary Ambient Air Quality Standards for Ozone.~~ The primary and secondary ambient air quality standard for ozone, measured and corrected for interferences due to nitrogen oxides and sulfur dioxide by the reference method described in 40 CFR Part 50, or by an equivalent method, is 240 micrograms per cubic meter (0.12 ppm) — and is expressed in a statistical form so that determination of attainment will be made when the expected number of days per calendar year with maximum hourly average concentrations above 235 µg/M³ (0.12 ppm) is equal to less than one.

(a) Primary and Secondary Ambient Air Quality Standards for Ozone:

1. The level of the 8-hour primary ambient air quality standard for ozone (O₃) is 0.070 parts per million (ppm), daily maximum 8-hour average,

measured by a reference method based on appendix D to 40 CFR Part 50 and designated in accordance with 40 CFR Part 53 or an equivalent method designated in accordance with 40 CFR Part 53.

2. The 8-hour primary O₃ ambient air quality standard is met at an ambient air quality monitoring site when the 3-year average of the annual fourth-highest daily maximum 8-hour average O₃ concentration is less than or equal to 0.070 ppm, as determined in accordance with appendix U to 40 CFR Part 50.

3. The level of the secondary ambient air quality standard for O₃ is 0.070 ppm, daily maximum 8-hour average, measured by a reference method based on appendix D to 40 CFR Part 50 and designated in accordance with 40 CFR Part 53 or an equivalent method designated in accordance with 40 CFR Part 53.

4. The 8-hour secondary O₃ ambient air quality standard is met at an ambient air quality monitoring site when the 3-year average of the annual fourth-highest daily maximum 8-hour average O₃ concentration is less than or equal to 0.070 ppm, as determined in accordance with appendix U to 40 CFR Part 50.

(5) ~~Primary and Secondary Ambient Air Quality Standards for Oxides of Nitrogen (Nitrogen Dioxide).~~ The primary and secondary ambient air quality standard for nitrogen dioxide, measured by the reference method described in 40 CFR Part 50, or by an equivalent method, is: 100 Micrograms per cubic meter (0.05 p.p.m.) — annual arithmetic mean.

(a) Primary and Secondary Ambient Air Quality Standards for Oxides of Nitrogen:

1. The level of the primary annual ambient air quality standard for oxides of nitrogen is 53 parts per billion (ppb, which is 1 part in 1,000,000,000), annual average concentration, measured in the ambient air as nitrogen dioxide.

2. The level of the primary 1-hour ambient air quality standard for oxides of nitrogen is 100 ppb, 1-hour average concentration, measured in the ambient air as nitrogen dioxide.

3. The level of the secondary ambient air quality standard for nitrogen dioxide is 0.053 parts per million (100 micrograms per cubic meter), annual arithmetic mean concentration.

4. The levels of the standards shall be measured by:

a. A reference method based on appendix F to 40 CFR Part 50; or

b. By a Federal equivalent method (FEM) designated in accordance with 40 CFR Part 53.

5. The annual primary standard is met when the annual average concentration in a calendar year is less than or equal to 53 ppb, as determined in accordance with appendix S of 40 CFR Part 50 for the annual standard.

6. The 1-hour primary standard is met when the three-year average of the annual 98th percentile of the daily maximum 1-hour average concentration is less than or equal to 100 ppb, as determined in accordance with appendix S of 40 CFR Part 50 for the 1-hour standard.

7. The secondary standard is attained when the annual arithmetic mean concentration in a calendar year is less than or equal to 0.053 ppm, rounded to three decimal places (fractional parts equal to or greater than 0.0005 ppm must be rounded up). To demonstrate attainment, an annual mean must be based upon hourly data that are at least 75 percent complete or upon data derived from manual methods that are at least 75 percent complete for the scheduled sampling days in each calendar quarter.

~~(6) Primary and Secondary Ambient Air Quality Standards for Lead. The primary and secondary ambient air quality standard for lead measured by the reference method described in 40 CFR Part 50, or by an equivalent method is: 1.5 micrograms per cubic meter—calendar quarter.~~

(a) The primary and secondary ambient air quality standards for lead (Pb) and its compounds are 0.15 micrograms per cubic meter, arithmetic mean concentration over a 3-month period, measured in the ambient air as Pb either by:

1. A reference method based on appendix G of 40 CFR Part 50 and designated in accordance with 40 CFR Part 53 or;

2. An equivalent method designated in accordance with 40 CFR Part 53.

(b) The primary and secondary ambient air quality standards for Pb are met when the maximum arithmetic 3-month mean concentration for a 3-year period, as determined in accordance with appendix R of 40 CFR Part 50, is less than or equal to 0.15 micrograms per cubic meter.

REGULATORY AUTHORITY

310 CMR 6.00: M.G.L. c. 111, § 142D.