

COMPLIANCE CHECKLIST**IP20 Respiratory Therapy**

The following checklist is intended to be used in the plan review applications for health care facilities submitted to the Massachusetts Department of Public Health. This checklist summarizes and references the applicable requirements from the Licensure Regulations and the 2022 Edition of the FGI Guidelines for Design and Construction of Hospitals. Applicants must verify compliance of the plans submitted to the Department with all referenced requirements from the Licensure Regulations and FGI Guidelines when completing this Checklist. A separate Checklist must be completed for each nursing unit, hospital or clinic department, or clinical suite.

Other jurisdictions, regulations and codes may have additional requirements which are not included in this checklist, such as:

- NFPA 101 Life Safety Code (2012) and applicable related standards contained in the appendices of the Code
- State Building Code (780 CMR)
- Accreditation requirements of The Joint Commission
- CDC Guidelines for Preventing the Transmission of Mycobacterium Tuberculosis in Health Care Facilities
- USP 797 & Regulations of the Massachusetts Board of Registration in Pharmacy
- Occupational Safety & Health Standards (OSHA)
- Accessibility Guidelines of the Americans with Disabilities Act (ADA)
- Architectural Access Board Regulations (521 CMR)
- Local Authorities having jurisdiction.

Instructions:

1. All requirement lines must be completed according to the following instructions and included in the plan submissions for Self-Certification Process or Abbreviated Review Process.
2. This checklist must be completed by the project architect or engineer based on the design actually reflected in the plans at the time of completion of the checklist.
3. Each requirement line (____) of this Checklist must be completed exclusively with one of the following marks, unless otherwise directed in the checklist. If a functional space is not affected by a renovation project, the mark "E" may be indicated on the requirement line (____) before the name of the functional space (associated requirements on indented lines below that name, or associated MEP requirements do not have to be completed in this case). If more than one functional space serves a given required function (e.g. patient room or exam room), that clarification should be provided in the Project Narrative, and the requirement lines are understood to only address the functional spaces that are involved in the project.

X = Requirement is met, for new space, for renovated space, or for existing direct support space for an expanded service.

☒ = Check box under section titles or individual requirements lines for optional services or functions that are not included in the project area.

E = Requirement relative to an existing suite or area that has been *licensed* for its designated function, is *not affected* by the construction project and *does not pertain to a required direct support space* for the specific service affected by the project. "E" must not be used for an existing required support space associated with a new patient care room or area.

W = Waiver requested for specific section of the Regulations or FGI Guidelines, where hardship in meeting requirement can be demonstrated (a Physical Plant Waiver Form must be completed for each waiver request). An explicit floor plan or plan detail must be attached to each waiver request.

4. All room functions marked with "X" must be shown on the plans with the same name labels as in this checklist.
5. Mechanical, electrical & plumbing requirements are only partially mentioned in this checklist. The relevant section of the FGI Guidelines must be used for project compliance with all MEP requirements and for waiver references.
6. Oxygen, vacuum, medical air, waste anesthesia gas disposal and instrument air outlets (if required) are identified respectively by the abbreviations "OX", "VAC", "MA", "WAGD" & "IA".
7. Requirements referenced with "FI" result from formal interpretations from the FGI Interpretations Task Group.
8. The location requirements including asterisks (*) refer to the definitions of the Glossary in the beginning section of the FGI Guidelines and reproduced in this checklist.

Facility Name:

DoN Project Number: (if applicable)

Facility Address:

Satellite Name: (if applicable)

Building/Floor Location:

Satellite Address: (if applicable)

Submission Dates:

Project Description:

Initial Date:

Revision Date:

Architectural Requirements**Building Systems Requirements**

2.2-3.9

RESPIRATORY THERAPY

2.2-3.9.2

LOCATIONS FOR COUGH-INDUCING & AEROSOL-GENERATING PROCEDURES☐ check if not included in project

2.2-3.9.2.1

- ☐ Rooms for cough-inducing procedures performed on patients who may have infectious mycobacterium tuberculosis
- ☐ equipped with local exhaust ventilation devices (e.g. booths or special enclosures that have discharge HEPA filters & exhaust directly to outside)

2.2-3.9.2.2

- ☐ ventilated booth
- ☐ air exchange rate is at least 12 air changes per hour
- ☐ min. exhaust airflow 50 CFM
- ☐ min. differential pressure 0.01" w.c.

2.2-3.9.2.3

- or**
- ☐ designated room that meets ventilation requirements for airborne infection control provided in Part 3

Ventilation:

- ☐ Min. 12 air changes per hour Table 7-1
- ☐ Exhaust
- ☐ Negative pressure
- ☐ No recirculating room units

2.2-3.9.3

OUTPATIENT TESTING & DEMONSTRATION SERVICES

2.2-3.9.3.1

- ☐ Reception & control station

2.2-3.9.3.2

- ☐ Room for patient testing education & demonstration

2.1-3.2.2.1

(1)

Space Requirements:**New Construction:**

- ☐ min. clear floor area 120 sf
- ☐ min. clear dimension 10'-0"

or**Renovation:**

- ☐ min. clear floor area 100 sf

(2)(a)

- ☐ room size permits room arrangement with min. clearance 3'-0" at each side & at foot of exam table, recliner or chair

2.1-3.2.2.2

(2)

- ☐ storage for supplies

(3)

- ☐ accommodations for written or electronic documentation

(4)

- ☐ space for visitor's chair

(5)

- ☐ handwashing station

2.2-3.1.3.6(2)(b)

- ☐ space for medical equipment
- ☐ view panel designed for patient visual privacy adjacent* to and/or in door

2.2-3.9.3.3

- ☐ Patient waiting area
- ☐ provision for patient using a wheelchair

Ventilation:

- ☐ Min. 6 air changes per hour Table 7-1

Lighting:

- ☐ Portable or fixed exam light 2.1-8.3.4.3(3)

Power:

- ☐ Min. 8 receptacles in total Table 2.1-1
- ☐ Min. 4 receptacles convenient to head of gurney or bed

Nurse Call System:

- ☐ Patient station Table 2.1-2

Medical Gases:

- ☐ 1 OX, 1 VAC, 1 MA per gurney Table 2.1-3

Architectural Requirements

- 2.2-3.9.3.4 ☐ Patient toilet room
 ☐ handwashing station

Building Systems Requirements

- Ventilation:
☐ Min. 10 air changes per hour Table 7-1
☐ Exhaust
☐ Negative pressure
☐ No recirculating room units

2.2-3.9.8 **SUPPORT AREAS FOR RESPIRATORY THERAPY SERVICES**

- 2.2-3.9.8.2 ☐ Reception & control station (may be combined with office & clerical space)
 (2)
 (1) ☐ permits visual control of waiting & activity areas
- 2.2-3.9.8.4 ☐ Office & clerical space
 ☐ provision be made for filing & retrieving patient records
- 2.2-3.9.8.12 Space & Utilities for Cleaning & Disinfecting Respiratory Therapy Equipment:
 (1) ☐ check if not included in project (only if equipment processing takes place in Sterile Processing Department)
- 2.2-3.9.8.12(2) Dedicated Reprocessing Room:
 (a) ☐ room arranged to provide soiled-to-clean workflow
- 2.2-3.9.8.12(2) ☐ work counters for drop-off soaking
 (b) ☐ tubs & pasteurization units
 ☐ documentation area
 ☐ handwashing station
- 2.1-5.1.2.3 ☐ consists of decontamination area & clean work area
 (1)
- (b) ☐ two entrances
 or
 ☐ single entrance
 ☐ located approximately equidistant from clean & decontamination sides of room
 ☐ allows for one-way traffic flow
- (2) ☐ decontamination area
 (a) ☐ countertop
 2.2-3.9.8.12(2) ☐ large sink for washing instruments
 (b) ☐ handwashing station
 ☐ separate from instrument-washing sink
 ☐ storage for supplies
 ☐ instrument air outlet for drying instruments
 or
 ☐ portable compressed air for drying instruments

- Ventilation:
☐ Min. 6 air changes per hour Table 7-1
☐ Exhaust
☐ Negative pressure
☐ No recirculating room units

Architectural Requirements**Building Systems Requirements**

- (b) ☐ instrument-washing sink separated from clean work area by 4'-0" distance from edge of sink
- or**
- ☐ instrument-washing sink separated from clean work area by wall
- or**
- ☐ instrument-washing sink separated from clean work area by screen
- ☐ screen extends min. 4'-0" above sink rim
- (3) ☐ clean work area
- (a) ☐ countertop
- (b) ☐ sterilizer
- (c) ☐ storage for supplies
- (d) ☐ instrument air outlet for drying instruments
- or**
- ☐ portable compressed air for drying instruments

Ventilation:

- ☐ Min. 4 air changes per hour Table 7-1
- ☐ Positive pressure
- ☐ No recirculating room units

2.2-3.9.8.13 ☐ Equipment & supply storage

2.2-3.9.9 **SUPPORT AREAS FOR STAFF**

2.2-3.9.9.2 ☐ Staff toilet room

☐ readily accessible* to respiratory service area

Ventilation:

- ☐ Min. 10 air changes per hour Table 7-1
- ☐ Exhaust
- ☐ Negative pressure
- ☐ No recirculating room units

2.2-3.9.9.3 ☐ Staff storage

☐ locking closets or cabinets provided immediately accessible* to each work area for securing staff personal effects

***LOCATION TERMINOLOGY:**

Directly accessible: Connected to the identified area or room through a doorway, pass-through, or other opening without going through an intervening room or public space

Adjacent: Located next to but not necessarily connected to the identified area or room

Immediately accessible: Available either in or adjacent to the identified area or room

Readily accessible: Available on the same floor or in the same clinic as the identified area or room

Architectural Details & MEP Requirements

2.1-7.2.2 **ARCHITECTURAL DETAILS**

2.1-7.2.2.1 **CORRIDOR WIDTH:**

NFPA 101, ☐ Aisles, corridors & ramps required for exit access in a hospital not less than 8'-0" in clear & unobstructed width

18.2.3.3 **or**

☐ Detailed code review incorporated in Project Narrative

2.1-7.2.2.2 (1)

(3)

☐ Aisles, corridors & ramps in adjunct areas not intended for the treatment or use of inpatients not less than 44" in clear & unobstructed width

CEILING HEIGHT:

- ☐ Min. ceiling height 7'-6" in corridors & in normally unoccupied spaces
- ☐ Min height 7'-6" above floor of suspended tracks rails & pipes located in traffic path for patients in beds & on stretchers
- ☐ Min ceiling height 7'-10" in other areas

- 2.1-7.2.2.3 DOORS & DOOR HARDWARE:
- (1) Door Type:
- (a) ☐ doors between corridors, rooms, or spaces subject to occupancy swing type or sliding doors
- (b) ☐ sliding doors
- ☐ check if not included in project
- ☐ manual or automatic sliding doors comply with NFPA 101
- ☐ detailed code review incorporated in Project Narrative
- ☐ no floor tracks
- (2) Door Opening:
- (a) ☐ min. 45.5" clear door width for diagnostic/treatment areas
- ☐ min. 83.5" clear door height for diagnostic/treatment areas
- (b) ☐ swinging doors for personnel use in addition to sliding doors
- ☐ check if not included in project
- ☐ min. clear width 34.5"
- (3) Door Swing:
- (a) ☐ doors do not swing into corridors except doors to non-occupiable spaces (e.g. environmental services rooms & electrical closets) & doors with emergency breakaway hardware
- (4) ☐ Lever hardware or push/pull latch hardware
- (5) Doors for Patient Toilet Facilities:
- (a) ☐ two separate doors
- or**
- ☐ door that swings outward
- or**
- ☐ door equipped with emergency rescue hardware (permits quick access from outside the room to prevent blockage of the door)
- or**
- ☐ sliding door other than pocket door
- (b) ☐ toilet room opens onto public area or corridor
- ☐ check if not included in project
- ☐ visual privacy is maintained

- 2.1-7.2.2.7 GLAZING MATERIALS:
- ☐ Glazing within 1 foot 6 inches of floor
- ☐ check if not included in project
- ☐ must be safety glass, wire glass or plastic break-resistant material

- 2.1-7.2.2.8 HANDWASHING STATIONS:
- (1)(c) ☐ Handwashing stations in patient care areas located so they are visible & unobstructed
- (3) ☐ Handwashing station countertops made of porcelain, stainless steel, solid-surface materials or impervious plastic laminate assembly
- (a) ☐ Countertops substrate
- ☐ check if not included in project
- ☐ marine-grade plywood (or equivalent material) with impervious seal
- (b) ☐ Handwashing station casework
- ☐ check if not included in project
- ☐ designed to prevent storage beneath sink
- (4) ☐ Provisions for drying hands
- ☐ check if not included in project (only in the case of hand scrub facilities)
- (5) ☐ hand-drying device does not require hands to contact dispenser
- (b) ☐ hand-drying device is enclosed to protect against dust or soil & to ensure single-unit dispensing
- (6) ☐ liquid or foam soap dispensers
- (7) ☐ No mirror at hand scrub stations or at handwashing stations in clean & sterile supply areas

- 2.1-7.2.2.9 GRAB BARS:
- (1) ☐ Grab bars anchored to sustain concentrated load 250 pounds
- (3) ☐ Ends of grab bars constructed to prevent snagging clothes of patients staff & visitors

- 2.1-7.2.2.10 HANDRAILS:
- (1) ☐ Handrails installed on both sides of patient use corridors
- (3) ☐ Rail ends return to wall or floor
- (4) ☐ Handrail gripping surfaces & fasteners are smooth (free of sharp or abrasive elements) with 1/8-inch min. radius
- (5) ☐ Handrails have eased edges & corners
- (6) ☐ Handrail finishes are cleanable

- 2.1-7.2.2.12 **NOISE CONTROL:**
 (1) ☐ Recreation rooms, exercise rooms equipment rooms & similar spaces where impact noises may be generated are not located directly over operating suites
or
☐ Special provisions are made to minimize impact noise
- (2) ☐ Noise reduction criteria in Table 1.2-6 applicable to partitions, floors & ceiling construction are met in patient areas
- 2.1-7.2.3 **SURFACES**
 2.1-7.2.3.1 **FLOORING & WALL BASES:**
 (1) ☐ Flooring surfaces cleanable & wear-resistant for location
 (3) ☐ Smooth transitions provided between different flooring materials
 (4) ☐ Flooring surfaces including those on stairways are stable, firm & slip-resistant
 (5) ☐ Floors & wall bases of soiled workrooms, toilet rooms & other areas subject to frequent wet cleaning are constructed of materials that are not physically affected by germicidal or other types of cleaning solutions
 (7)(a) Floors are monolithic & integral coved wall bases are at least 6" high & tightly sealed to wall in rooms listed below:
☐ airborne infection isolation (All) room
☐ soiled workroom & soiled holding room
- 2.1-7.2.3.2 **WALLS & WALL PROTECTION:**
 (1)(a) ☐ Wall finishes are washable
 (1)(b) ☐ Wall finishes near plumbing fixtures are smooth, scrubbable & water-resistant
 (2) ☐ Wall surfaces in areas routinely subjected to wet spray or splatter (e.g. environmental services rooms) are monolithic or have sealed seams that are tight & smooth
 (5) ☐ Wall protection devices & corner guards durable & scrubbable
- 2.1-7.2.3.3 **CEILINGS:**
 (1) ☐ Ceilings provided in all areas except mechanical, electrical & communications equipment rooms
 (a) ☐ Ceilings cleanable with routine housekeeping equipment
 (b) ☐ Acoustic & lay-in ceilings where used do not create ledges or crevices

- 2.1-7.2.4 **FURNISHINGS:**
 2.1-7.2.4.1 ☐ built-in furnishings upholstered with impervious materials in patient treatment areas with risks of exposure & contamination from bodily fluids & other fluids
 2.1-7.2.4.3 ☐ Privacy curtains in patient care areas are washable
- 2.1-8.2 **HEATING VENTILATION & AIR-CONDITIONING (HVAC) SYSTEMS UTILITIES:**
 Part 3/6.1 Ventilation Upon Loss of Electrical Power:
 Part 3/6.1.1 ☐ space ventilation & pressure relationship requirements of Table 7-1 are maintained for All Rooms PE Rooms Operating Rooms in event of loss of normal electrical power
- Part 3/6.1.2 Heating & Cooling Sources:
 Part 3/6.1.2.1 ☐ heat sources & essential accessories provided in number & arrangement sufficient to accommodate facility needs (reserve capacity) even when any one of heat sources or essential accessories is not operating due to breakdown or routine maintenance
☐ capacity of remaining source or sources is sufficient to provide heating for operating rooms & recovery rooms
- Part 3/6.1.2.2 Central cooling systems greater than 400 tons (1407 kW) peak cooling load
☐ check if not included in project
☐ number & arrangement of cooling sources & essential accessories is sufficient to support owner's facility operation plan upon breakdown or routine maintenance of any one of cooling sources.
- Part 3/6.2 **AIR-HANDLING UNIT (AHU) DESIGN:**
 Part 3/6.2.1 ☐ AHU casing is designed to prevent water intrusion resist corrosion & permit access for inspection & maintenance

Part 3/6.3 OUTDOOR AIR INTAKES & EXHAUST DISCHARGES:

Part 3/6.3.1 Outdoor Air Intakes:

- Part 3/6.3.1.1
- ☐ located such that shortest distance from intake to any specific potential outdoor contaminant source be equal to or greater than separation distance listed in Table 6-1
 - ☐ located min of 25'-0" from cooling towers & all exhaust & vent discharges
 - ☐ air intakes located away from public access
 - ☐ all intakes are designed to prevent entrainment of wind-driven rain
 - ☐ contain features for draining away precipitation
 - ☐ equipped with birdscreens of mesh no smaller than 0.5 in

- Part 3/6.3.1.4
- ☐ intake in areaway
 - ☐ check if not included in project
 - ☐ bottom of areaway air intake opening is at least 6'-0" above grade
 - ☐ bottom of air intake opening from areaway into building is at least 3'-0" above bottom of areaway

Part 3/6.3.2 Exhaust Discharges:

- Part 3/6.3.2.1
- ☐ ductwork within building is under negative pressure for exhaust of contaminated air (i.e. air from All rooms)
 - ☐ exhaust discharge outlets with contaminated air located such that they reduce potential for recirculation of exhausted air back into building

- Part 3/6.3.2.2
- ☐ exhaust discharge outlets with contaminated air additionally is arranged to discharge to atmosphere in vertical direction at least 10'-0" above adjoining roof level
 - ☐ exhaust discharge outlets from All rooms, bronchoscopy & sputum collection exhaust & laboratory work area chemical fume hoods is located not less than 25'-0" horizontally from outdoor air intakes openable windows/doors & areas that are normally accessible to public

Part 3/6.4 FILTRATION:

- a. ☐ Particulate matter filters, minimum MERV-8 provided upstream of first heat exchanger surface of any air-conditioning system that combines return air from multiple rooms or introduces outdoor air.
- b. ☐ Outdoor air filtered in accordance with Table 7-1
- c. ☐ Air supplied from equipment serving multiple or different spaces is filtered in accordance with Table 7-1
- d. ☐ Air recirculated within room is filtered in accordance with Table 7-1, or Section 7.1(a)(5)
- e. ☐ Design includes all necessary provisions to prevent moisture accumulating on filters located downstream of cooling coils & humidifiers
- h. ☐ For spaces that do not permit air recirculated by means of room units & have minimum filter efficiency of MERV-14, MERV-16 or HEPA in accordance with Table 7-1, the min. filter requirement listed in Table 7-1, is installed downstream of all wet-air cooling coils & supply fan

Part 3/6.5 HEATING & COOLING SYSTEMS:

- Part 3/6.5.3
- ☐ Radiant heating systems
 - ☐ check if not included in project
 - ☐ ceiling or wall panels with exposed cleanable surfaces or radiant floor heating are provided in All room, PE room, operating room or procedure room

Part 3/6.7 AIR DISTRIBUTION SYSTEMS:

- Part 3/6.7.1
- ☐ Maintain pressure relationships required in tables 7.1 in all modes of HVAC system operation
 - ☐ Spaces that have required pressure relationships are served by fully ducted return systems or fully ducted exhaust systems
 - ☐ Inpatient facilities & recovery rooms are served by fully ducted return or exhaust systems

Part 3/6.7.2 Air Distribution Devices:

- ☐ supply air outlets comply with Table 6-2

Part 3/6.7.3 Smoke Barriers:

- ☐ HVAC zones coordinated with compartmentation to minimize ductwork penetrations of fire & smoke barriers.

Part 3/6.8 ENERGY RECOVERY SYSTEMS:

☐ check if not included in project
Part 3/6.8.1 ☐ Located upstream of filters required by Part 3/6.8.4

Part 3/7 SPACE VENTILATION—HOSPITAL SPACES:

Part 3/7.1.a ☐ Spaces ventilated according to Table 7-1Part 3/7.1.a.1 ☐ Air movement is from clean to less-clean areasPart 3/7.1.a.3 ☐ Min number of total air changes required for positive pressure rooms is provided by total supply airflow
☐ Min number of total air changes required for negative pressure rooms is provided by total exhaust airflowPart 3/7.1.a.4 ☐ Entire min. outdoor air changes per hour required by Table 7-1 for each space meet filtration requirements of Section 6.4Part 3/7.1.a.5 ☐ Air recirculation through room unit
☐ check if not included in project
☐ complies with Table 7-1
☐ room unit receive filtered & conditioned outdoor air
☐ serve only single space
☐ provides min MERV 8 filter
☐ located upstream of any cold surface so that all of air passing over cold surface is filtered

Part 3/7.2 ADDITIONAL ROOM-SPECIFIC REQUIREMENTS:

Part 3/7.2.1 Airborne Infection Isolation (All) Rooms

☐ check if not included in project

- ☐ All rooms have permanently installed device and/or mechanism to constantly monitor differential air pressure between room & corridor
- ☐ Local visual means is provided to indicate whenever negative differential pressure is not maintained
- ☐ Air from All room is exhausted directly to outdoors

Exhaust air from All rooms, associated anterooms & toilet rooms:

☐ is discharged directly to outdoors without mixing with exhaust air from any other non-All room or exhaust system

or

☐ is discharged into the general exhaust stream, provided the All room exhaust air first passes through a HEPA filter (all exhaust ductwork kept under negative pressure)

☐ Exhaust air grille or register in patient room is located directly above patient bed on ceiling or on wall near head of bed

☐ Anteroom

☐ check if not included in project

☐ All room is at negative pressure with respect to anteroom

☐ Anteroom is at negative pressure with respect to corridor

2.1-8.3

ELECTRICAL SYSTEMS

2.1-8.3.2

ELECTRICAL DISTRIBUTION & TRANSMISSION2.1-8.3.2.2
(1)

Panelboards:

☐ panelboards serving life safety branch circuits serve floors on which they are located & floors immediately above & below

(2)

☐ panelboard critical branch circuits serve floors on which they are located

(3)

☐ panelboards not located in exit enclosures or exit passageways

2.1-8.3.3

POWER-GENERATING & -STORING EQUIPMENT

2.1-8.3.3.1

☐ Essential electrical system or emergency electrical power

(1)

☐ essential electrical system complies with NFPA 99

(2)

☐ emergency electrical power complies with NFPA 99

2.1-8.3.4

2.1-8.3.4.1(1)

LIGHTING

☐ Luminaires in patient areas have smooth, cleanable, impact-resistant lenses concealing light source

2.1-8.3.4.1(2)

☐ Luminaires designed to dissipate heat such that touchable surfaces will not burn occupants or ignite materials.

(7)

☐ Uplight fixtures installed in patient care areas are covered

2.1-8.3.5

2.1-8.3.5.1

ELECTRICAL EQUIPMENT

☐ Handwashing sinks & scrub sinks that depends on building electrical service for operation are connected to essential electrical system

2.1-8.3.5.2

☐ Electronic health record system servers & centralized storage provided with uninterruptible power supply

2.1-8.3.6	ELECTRICAL RECEPTACLES
2.1-8.3.6.1	Receptacles In Corridors:
(1)	<input type="checkbox"/> duplex-grounded receptacles for general use installed 50'-0" apart or less in all corridors <input type="checkbox"/> duplex-grounded receptacles for general use installed within 25'-0" of corridor ends
2.1-8.3.6.3	Essential Electrical System Receptacles:
(1)	<input type="checkbox"/> cover plates for electrical receptacles supplied from essential electrical system are distinctively colored or marked for identification
(2)	<input type="checkbox"/> same color is used throughout facility
2.1-8.4	PLUMBING SYSTEMS
2.1-8.4.2	Plumbing & Other Piping Systems:
2.1-8.4.2.1(3)	<input type="checkbox"/> no plumbing piping exposed overhead or on walls where possible accumulation of dust or soil may create cleaning problem
2.1-8.4.2.5	Heated Potable Water Distribution Systems:
(2)	<input type="checkbox"/> heated potable water distribution systems serving patient care areas are under constant recirculation <input type="checkbox"/> non-recirculated fixture branch piping does not exceed 25'-0" in length
(3)(a)	<input type="checkbox"/> no installation of dead-end piping (except for empty risers mains & branches for future use)
(3)(c)	<input type="checkbox"/> any existing dead-end piping is removed
(3)(b)	<input type="checkbox"/> check if <u>not</u> included in project
(4)(a)	<input type="checkbox"/> water-heating system supplies water at temperatures & amounts indicated in Table 2.1-4
2.1-8.4.2.6	Drainage Systems:
(1)(a)	<input type="checkbox"/> drainage piping installed above ceiling of or exposed in rooms listed below piping have special provisions (e.g double wall containment piping or oversized drip pans) to protect space below from leakage & condensation <ul style="list-style-type: none"> • operating rooms • delivery rooms • procedure rooms • trauma rooms • nurseries • central kitchens

	<ul style="list-style-type: none"> • one-room sterile processing facilities • clean workroom of two-room sterile processing facilities • pharmacies • Class 2 & 3 imaging rooms • electronic mainframe rooms (EFs & TERs) • main switchgear • electrical rooms • electronic data processing areas • electric closets
(1)(b)	<input type="checkbox"/> drip pan for drainage piping above ceiling of sensitive area <input type="checkbox"/> check if <u>not</u> included in project <input type="checkbox"/> accessible <input type="checkbox"/> overflow drain with outlet located in normally occupied area that is not open to restricted area
2.1-8.4.3	PLUMBING FIXTURES
2.1-8.4.3.1(1)	<input type="checkbox"/> Materials used for plumbing fixtures are non-absorptive & acid-resistant
2.1-8.4.3.2	Handwashing Station Sinks:
(1)	<input type="checkbox"/> designed with basins & faucets that reduce risk of splashing to areas where direct patient care is provided, sterile procedures are performed, medications are prepared or food is prepared
(2)	<input type="checkbox"/> sink basins have nominal size of no less than 144 square inches
	<input type="checkbox"/> sink basins have min dimension 9 inches in width or length
(3)	<input type="checkbox"/> sink basins are made of porcelain stainless steel or solid-surface materials
(5)	<input type="checkbox"/> water discharge point of faucets is at least 10" above bottom of basin
(7)	<input type="checkbox"/> anchored so that allowable stresses are not exceeded where vertical or horizontal force of 250 lbs is applied
(8)	<input type="checkbox"/> sinks used by medical & nursing staff patients & public have fittings that can be operated without using hands (may be single-lever or wrist blade devices)
(a)	<input type="checkbox"/> blade handles <input type="checkbox"/> check if <u>not</u> included in project <input type="checkbox"/> at least 4 inches in length <input type="checkbox"/> provide clearance required for operation

- (b) ☐ sensor-regulated water fixtures
☐ check if not included in project
☐ meet user need for temperature & length of time water flows
☐ designed to function at all times & during loss of normal power

- 2.1-8.4.3.4 Ice-Making Equipment:
☐ copper tubing provided for supply connections to ice-making equipment

- 2.1-8.4.3.5 Clinical Sinks:
 (1) ☐ trimmed with valves that can be operated without hands (may be single-lever or wrist blade devices)
 (a) ☐ handles are at least 6 in long
 (b) ☐ integral trap wherein upper portion of water trap provides visible seal
 (2) ☐

- 2.1-8.4.4 **MEDICAL GAS & VACUUM SYSTEMS**
☐ Station outlets provided as indicated in Table 2.1-3

- 2.1-8.5.1 **CALL SYSTEMS**
 2.1-8.5.1.1(1) ☐ Nurse call stations provided as required in Table 2.1-2
 2.1-8.5.1.1(2) ☐ Nurse call systems report to attended location with electronically supervised visual & audible annunciation as indicated in Table 2.1-2
 2.1-8.5.1.1(4) ☐ Call system complies with UL 1069 "Standard for Hospital Signaling & Nurse Call Equipment"
 2.1-8.5.1.1(5) ☐ Wireless nurse call system
☐ check if not included in project
☐ complies with UL 1069
 2.1-8.5.1.2(4) ☐ Nurse call system provided in each patient care area as required in Table 2.1-2

- 2.1-8.5.1.3 Bath Stations:
☐ bath station that can be activated by patient lying on floor provided at each patient toilet
 (1) ☐ alarm in these areas can be turned off only at bath station where it was initiated
 (3) ☐ toilet bath stations located on the side of toilets within 12" of front of toilet bowl & 3'-0" to 4'-0" above floor

- 2.1-8.5.1.5 ☐ Emergency call stations are equipped with continuous audible or visual confirmation to person who initiated the code call

2.1-8.5.3 **EMERGENCY COMMUNICATION SYSTEM**

- ☐ Emergency-radio communication system provided in each facility
 2.1-8.5.3.1 ☐ operates independently of building's service & emergency power systems during emergencies
 2.1-8.5.3.2 ☐ frequency capabilities to communicate with state emergency communication networks

2.1-8.6.2 **ELECTRONIC SURVEILLANCE SYSTEMS**

- ☐ check if not included in project
 2.1-8.6.2.1 ☐ Display screens in patient areas are mounted in tamper-resistant enclosure that is unobtrusive
 2.1-8.6.2.2 ☐ Display screens are located so they are not readily observable by general public or patients
 2.1-8.6.2.3 ☐ Electronic surveillance systems receive power from essential electrical system