

COMPLIANCE CHECKLIST**IP24 Pharmacy Services**

The following checklist is intended to be used in the plan review applications for health care facilities submitted to the Massachusetts Department of Public Health. This checklist summarizes and references the applicable requirements from the Licensure Regulations and the 2018 Edition of the FGI Guidelines for Design and Construction of Hospitals. Applicants must verify compliance of the plans submitted to the Department with all referenced requirements from the Licensure Regulations and FGI Guidelines when completing this Checklist. A separate Checklist must be completed for each nursing unit, hospital or clinic department, or clinical suite.

Other jurisdictions, regulations and codes may have additional requirements which are not included in this checklist, such as:

- NFPA 101 Life Safety Code (2012) and applicable related standards contained in the appendices of the Code
- State Building Code (780 CMR)
- Accreditation requirements of The Joint Commission
- CDC Guidelines for Preventing the Transmission of Mycobacterium Tuberculosis in Health Care Facilities
- USP 797, USP 800 & Regulations of the Massachusetts Board of Registration in Pharmacy
- Occupational Safety & Health Standards (OSHA)
- Accessibility Guidelines of the Americans with Disabilities Act (ADA)
- Architectural Access Board Regulations (521 CMR)
- Local Authorities having jurisdiction.

Instructions:

1. All requirement lines must be completed according to the following instructions and included in the plan submissions for Self-Certification Process or Abbreviated Review Process.
2. This checklist must be completed by the project architect or engineer based on the design actually reflected in the plans at the time of completion of the checklist.
3. Each requirement line (____) of this Checklist must be completed exclusively with one of the following marks, unless otherwise directed in the checklist. If a functional space is not affected by a renovation project, the mark "E" may be indicated on the requirement line (____) before the name of the functional space (associated requirements on indented lines below that name, or associated MEP requirements do not have to be completed in this case). If more than one functional space serves a given required function (e.g. patient room or exam room), that clarification should be provided in the Project Narrative, and the requirement lines are understood to only address the functional spaces that are involved in the project.

X = Requirement is met, for new space, for renovated space, or for existing direct support space for an expanded service.

☒ = Check box under section titles or individual requirements lines for optional services or functions that are not included in the project area.

E = Requirement relative to an existing suite or area that has been *licensed* for its designated function, is *not affected* by the construction project and *does not pertain to a required direct support space* for the specific service affected by the project. "E" must not be used for an existing required support space associated with a new patient care room or area.

W = Waiver requested for specific section of the Regulations or FGI Guidelines, where hardship in meeting requirement can be demonstrated (a Physical Plant Waiver Form must be completed for each waiver request). An explicit floor plan or plan detail must be attached to each waiver request.

4. All room functions marked with "X" must be shown on the plans with the same name labels as in this checklist.
5. Mechanical, electrical & plumbing requirements are only partially mentioned in this checklist. The relevant section of the FGI Guidelines must be used for project compliance with all MEP requirements and for waiver references.
6. Oxygen, vacuum, medical air, waste anesthesia gas disposal and instrument air outlets (if required) are identified respectively by the abbreviations "OX", "VAC", "MA", "WAGD" & "IA".
7. Requirements referenced with "FI" result from formal interpretations from the FGI Interpretations Task Group.
8. The location requirements including asterisks (*) refer to the definitions of the Glossary in the beginning section of the FGI Guidelines and reproduced in this checklist.

Facility Name:

DoN Project Number: (if applicable)

Facility Address:

Satellite Name: (if applicable)

Building/Floor Location:

Satellite Address: (if applicable)

Submission Dates:

Project Description:

Initial Date:

Revision Date:

	Architectural Requirements	Building Systems Requirements
2.1-4.2	PHARMACY SERVICES	
2.1-4.2.1.2	LOCATION	
(1)	___ Pharmacy room or suite accessible to clinical areas of hospital	
(2)	___ Controlled access to pharmacy room or suite	
2.1-4.2.2	PHARMACY AREAS	
2.1-4.2.2.1	___ Dispensing facilities	
(1)	___ room or area for receiving unpacking & inventory control of materials used in pharmacy	Ventilation: ___ Min. 4 air changes per hour ___ Positive pressure
(2)	___ work counters & space for automated & manual dispensing activities	
(3)	___ extemporaneous compounding area ___ sink & counter space for drug preparation	
(4)	___ area for reviewing & recording	
(5)	___ area for temporary storage exchange & restocking of carts	
(6)	___ security provisions for drugs & personnel in dispensing counter area	
2.1-4.2.2.2	___ Manufacturing facilities	
(1)	___ bulk compounding area	Ventilation:
(2)	___ provisions for packaging & labeling	___ Min. 4 air changes per hour
(3)	___ quality control area	___ Positive pressure
2.1-4.2.2.3	___ Storage (storage cabinets, shelves or separate rooms or closets)	
(1)	___ bulk storage	Ventilation:
(2)	___ active storage	___ Min. 4 air changes per hour
(3)	___ refrigerated storage	___ Positive pressure
(4)	___ storage for volatile fluids & alcohol	
(5)	___ secured lockable storage for narcotics & controlled drugs	
(6)	___ equipment & supply storage for general supplies & equipment not in use	
2.1-4.2.3	STERILE WORK AREAS	
	<input type="checkbox"/> check if <u>not</u> included in project	
2.1-4.2.3.1		
(1)	___ Layout of pharmacy precludes unrelated traffic through non-hazardous drug IV preparation rooms & hazardous drug IV preparation rooms	
(2)	___ Positive pressure non-hazardous IV preparation room & negative pressure hazardous drug IV prep room do not share robotic systems	

Architectural Requirements**Building Systems Requirements**

- 2.1-4.2.3.2 _____ Non-hazardous IV preparation area
 ☐ check if not included in project
 _____ laminar-flow workstation designed for product protection
- (1) _____ laminar-flow workstation includes non-hydroscopic filter rated at 99.97 percent (HEPA filter)
- (2) _____ laminar-flow workstation have visible pressure gauge for detection of filter leaks or defects
 _____ complies with regulations of Board of Registration in Pharmacy 247 CMR 17.00
- 2.1-4.2.3.3 _____ Hazardous drug IV preparation room
 ☐ check if not included in project
 _____ separate room provided for preparation of hazardous drug IV admixtures under class II (type A2 B1 or B2) or class III biological safety cabinet
 _____ complies with regulations of Board of Registration in Pharmacy 247 CMR 19.00

SUPPORT AREAS FOR PHARMACY

- 2.1-4.2.8.2 _____ Separate room or area provided for office functions
- 2.1-4.2.8.3 _____ Room for education & training (may be multipurpose room shared w/ other departments)
- 2.1-4.2.8.4 _____ Outpatient medication consultation area
 ☐ check if not included in project (only if medications are not dispensed to outpatients from hospital pharmacy area)
- 2.1-4.2.8.7 _____ Handwashing station
 _____ provided either in anteroom or immediately outside room where open medications are prepared
- 2.1-4.2.8.13 _____ Unit dose procedure used
 ☐ check if not included in project
 _____ additional equipment & supply storage
 _____ space for carts

SUPPORT AREAS FOR STAFF

- 2.1-4.2.9 (may be outside pharmacy area & shared with other departments)
- 2.1-4.2.9.2 _____ Readily accessible* to pharmacy
- 2.1-4.2.9.1 _____ Lounge
 _____ Locker facilities
 _____ Staff toilet room

Ventilation:

- _____ Min. 10 air changes per hour Table 7.1
 _____ Exhaust
 _____ Negative pressure
 _____ No recirculating room units

***LOCATION TERMINOLOGY:**

Directly accessible: Connected to the identified area or room through a doorway, pass-through, or other opening without going through an intervening room or public space

Adjacent: Located next to but not necessarily connected to the identified area or room

Immediately accessible: Available either in or adjacent to the identified area or room

Readily accessible: Available on the same floor or in the same clinic as the identified area or room

Architectural Details & MEP Requirements

2.1-7.2.2	ARCHITECTURAL DETAILS	(b)	Countertops substrate
2.1-7.2.2.1	CORRIDOR WIDTH:		<input type="checkbox"/> check if <u>not</u> included in project
NFPA 101, 18.2.3.4	<input type="checkbox"/> Aisles, corridors & ramps in adjunct areas not intended for the housing, treatment, or use of inpatients not less than 44" in clear & unobstructed width		<input type="checkbox"/> marine-grade plywood (or equivalent material) with impervious seal
	or	(4)	Handwashing station casework
	<input type="checkbox"/> Detailed code review incorporated in Project Narrative		<input type="checkbox"/> check if <u>not</u> included in project
2.1-7.2.2.2	CEILING HEIGHT:	(5)	Provisions for drying hands
(1)	<input type="checkbox"/> Min ceiling height 7'-6" in corridors & in normally unoccupied spaces		<input type="checkbox"/> check if <u>not</u> included in project (only at hand scrub facilities)
	<input type="checkbox"/> Min. ceiling height 7'-10" in other areas	(a)	<input type="checkbox"/> hand-drying device does not require hands to contact dispenser
2.1-7.2.2.3	DOORS & DOOR HARDWARE:	(b)	<input type="checkbox"/> hand-drying device is enclosed to protect against dust or soil & to ensure single-unit dispensing
(1)	Door Type:	(6)	<input type="checkbox"/> Liquid or foam soap dispensers
(a)	<input type="checkbox"/> doors between corridors, rooms, or spaces subject to occupancy swing type or sliding doors	2.1-7.2.3	SURFACES
(b)	<input type="checkbox"/> sliding doors	2.1-7.2.3.1	FLOORING & WALL BASES:
	<input type="checkbox"/> <input type="checkbox"/> check if <u>not</u> included in project	(1)	<input type="checkbox"/> Flooring surfaces cleanable & wear-resistant for location
	<input type="checkbox"/> manual or automatic sliding doors comply with NFPA 101	(3)	<input type="checkbox"/> Smooth transitions provided between different flooring materials
	<input type="checkbox"/> detailed code review incorporated in Project Narrative	(4)	<input type="checkbox"/> Flooring surfaces including those on stairways are stable, firm & slip-resistant
	<input type="checkbox"/> no floor tracks	(5)	<input type="checkbox"/> Floors & wall bases of toilet rooms & other areas subject to frequent wet cleaning are constructed of materials that are not physically affected by germicidal or other types of cleaning solutions
(3)	Door Swing:	(7)(a)	<input type="checkbox"/> Floors are monolithic & integral coved wall bases are at least 6" high & tightly sealed to wall in IV & chemotherapy preparation rooms
(a)	<input type="checkbox"/> doors do not swing into corridors except doors to non-occupiable spaces	2.1-7.2.3.2	WALLS & WALL PROTECTION:
(4)	<input type="checkbox"/> Lever hardware or push/pull latch hardware	(1)(a)	<input type="checkbox"/> Wall finishes are washable
2.1-7.2.2.7	GLAZING MATERIALS:	(1)(b)	<input type="checkbox"/> Wall finishes near plumbing fixtures are smooth, scrubbable & water-resistant
	<input type="checkbox"/> Glazing within 1 foot 6 inches of floor must be safety glass, wire glass or plastic break-resistant material		
2.1-7.2.2.8	HANDWASHING STATIONS:		
(3)(a)	<input type="checkbox"/> Handwashing station countertops made of porcelain, stainless steel, solid-surface materials or impervious plastic laminate assembly		

- (2) _____ Wall surfaces in areas routinely subjected to wet spray or splatter (e.g. environmental services rooms) are monolithic or have sealed seams that are tight & smooth

- (5) _____ Wall protection devices & corner guards durable & scrubbable

2.1-7.2.3.3 **CEILINGS:**

- (1) _____ Ceilings provided in all areas except mechanical, electrical & communications equipment rooms
- (a) _____ Ceilings cleanable with routine housekeeping equipment
- (b) _____ Acoustic & lay-in ceilings where used not create ledges or crevices

- (2) _____ Semi-Restricted Areas:

☐ check if not included in project

- (a) _____ ceiling finishes are scrubbable, non absorptive, non perforated, & capable of withstanding cleaning with chemicals

- (b) _____ lay-in ceilings
_____ gasketed or each ceiling tile weighs at least one pound per square foot

- (c) _____ use of perforated tegular serrated or highly textured tiles not are permitted in semi-restricted areas

or

_____ ceilings of monolithic construction

2.1-8.2 **HEATING VENTILATION & AIR-CONDITIONING (HVAC) SYSTEMS**

Part 3/6.1.2 Heating & Cooling Sources:

- Part 3/6.1.2.1 _____ provide heat sources & essential accessories in number & arrangement sufficient to accommodate facility needs (reserve capacity) even when any one of heat sources or essential accessories is not operating due to breakdown or routine maintenance

- Part 3/6.1.2.2 Central cooling systems greater than 400 tons (1407 kW) peak cooling load
☐ check if not included in project
_____ number & arrangement of cooling sources & essential accessories is sufficient to support facility operation plan upon breakdown or routine maintenance of any one of cooling sources.

- Part 3/6.2 **AIR-HANDLING UNIT (AHU) DESIGN:**
Part 3/6.2.1 _____ AHU casing is designed to prevent water intrusion, resist corrosion & permit access for inspection & maintenance

Part 3/6.3 **OUTDOOR AIR INTAKES & EXHAUST DISCHARGES:**

- Part 3/6.3.1 Outdoor Air Intakes:
Part 3/6.3.1.1 _____ located min. of 25 ft from cooling towers & all exhaust & vent discharges
_____ outdoor air intakes located such that bottom of air intake is at least 6 ft above grade
_____ facilities with moderate-to-high risk of natural or man-made extraordinary incidents locate new air intakes away from public access

- Part 3/6.3.1.3 _____ intakes on top of buildings
☐ check if not included in project
_____ located with bottom of air intake min. of 3 ft above roof level

- Part 3/6.3.1.4 _____ intake in areaway
☐ check if not included in project
_____ bottom of areaway air intake opening is at least 6 ft above grade
_____ bottom of air intake opening from areaway into building is at least 3 ft above bottom of areaway

- Part 3/6.3.2 Exhaust Discharges:
Part 3/6.3.2.1 _____ ductwork within building is under negative pressure for exhaust of contaminated air (i.e. air from pharmacy hazardous-drug exhausted enclosures)
_____ exhaust discharge outlets with contaminated air located such that they reduce potential for recirculation of exhausted air back into building
Part 3/6.3.2.2 _____ exhaust discharge outlets with contaminated air arranged to discharge to atmosphere in vertical direction at least 10 ft above adjoining roof level
_____ exhaust discharge outlets from pharmacy hazardous-drug exhausted enclosures discharge with stack velocity of at least 2500 fpm

- _____ exhaust discharge outlets from pharmacy hazardous-drug exhausted enclosures is located not less than 25 ft horizontally from outdoor air intakes, openable windows/doors & areas that are normally accessible to public
- Part 3/6.4 **FILTRATION:**
- _____ Two filter banks for inpatient care (see Table 6.4)
- _____ Filter Bank No. 1: MERV 7
- _____ Filter Bank No. 2: MERV 14
- _____ Each filter bank with efficiency of greater than MERV 12 is provided with differential pressure measuring device to indicate when filter needs to be changed
- Part 3/6.4.1 _____ Filter Bank No. 1 is placed upstream of heating & cooling coils
- Part 3/6.4.2 _____ Filter Bank No. 2 is placed downstream of all wet-air cooling coils & supply fan
- Part 3/6.7 **AIR DISTRIBUTION SYSTEMS:**
- Part 3/6.7.1 _____ Maintain pressure relationships required in tables 7.1 in all modes of HVAC system operation
- _____ Spaces that have required pressure relationships are served by fully ducted return systems or fully ducted exhaust systems
- Part 3/6.7.2 **Air Distribution Devices:**
- _____ supply air outlets comply with Table 6.7.2
- Part 3/6.7.3 **Smoke Barriers:**
- _____ HVAC zones coordinated with compartmentation to minimize ductwork penetrations of fire & smoke barriers.
- Part 3/6.8 **ENERGY RECOVERY SYSTEMS:**
- ☐ check if not included in project
- Part 3/6.8.1 _____ Located upstream of Filter Bank No. 2
- Part 3/6.8.3 _____ Energy recovery systems with leakage potential
- ☐ check if not included in project
- _____ arranged to minimize potential to transfer exhaust air directly back into supply airstream
- _____ designed to have no more than 5% of total supply airstream consisting of exhaust air
- _____ not used from these exhaust airstream sources: general hazardous material storage
- Part 3/7 **SPACE VENTILATION**
- Part 3/7.1.a _____ Complies with Table 7.1
- _____ Air movement is from clean to less-clean areas
- Part 3/7.1.a.1 _____

- Part 3/7.1.a.3 _____ Min. number of total air changes required for positive pressure rooms is provided by total supply airflow
- _____ Min. number of total air changes required for negative pressure rooms is provided by total exhaust airflow
- Part 3/7.1.a.4 _____ Entire minimum outdoor air changes per hour required by Table 7.1 for each space meet filtration requirements of Section 6.4
- Part 3/7.1.a.5 _____ Air recirculation through room unit
- ☐ check if not included in project
- _____ complies with Table 7.1
- _____ room unit receive filtered & conditioned outdoor air
- _____ serve only a single space
- _____ provides min. MERV 6 filter located upstream of any cold surface so that all of air passing over cold surface is filtered

2.1-8.3 ELECTRICAL SYSTEMS

2.1-8.3.2 ELECTRICAL DISTRIBUTION & TRANSMISSION

- 2.1-8.3.2.1 **Switchboards Switchgear & Automatic Transfer Switches:**
- (1)(b) _____ accessible to authorized persons only
- (1)(c) _____ located in dry ventilated space free of corrosive or explosive fumes, gases or any flammable material
- (2) _____ overload protective devices are listed for ambient room temperature for space in which they are installed
- 2.1-8.3.2.2 **Panelboards:**
- (1) _____ panelboards serving life safety branch circuits serve floors on which they are located & floors immediately above & below
- (2) _____ panelboard critical branch circuits serve floors on which they are located
- (3) _____ panelboards not located in exit enclosures or exit passageways

2.1-8.3.3 POWER-GENERATING & -STORING EQUIPMENT

- 2.1-8.3.3.1 _____ Essential electrical system or emergency electrical power
- (1) _____ essential electrical system complies with NFPA 99
- (2) _____ emergency electrical power complies with NFPA 99

2.1-8.3.5 ELECTRICAL EQUIPMENT

- 2.1-8.3.5.1 ☐ Handwashing sinks that depends on building electrical service for operation are connected to essential electrical system
☐ check if not included in project
- 2.1-8.3.5.2 ☐ Electronic health record system servers & centralized storage provided with uninterruptible power supply

2.1-8.3.6 ELECTRICAL RECEPTACLES

- 2.1-8.3.6.1 Receptacles In Corridors:
 (1) ☐ duplex-grounded receptacles for general use installed 50'-0" apart or less in all corridors
☐ duplex-grounded receptacles for general use installed within 25'-0" of corridor ends
- 2.1-8.3.6.3 Essential Electrical System Receptacles:
 (1) ☐ cover plates for electrical receptacles supplied from essential electrical system are distinctively colored or marked for identification
 (2) ☐ same color is used throughout facility

2.1-8.4 PLUMBING SYSTEMS

- 2.1-8.4.2 Plumbing & Other Piping Systems:
 2.1-8.4.2.1(3) ☐ no plumbing piping exposed overhead or on walls where possible accumulation of dust or soil may create cleaning problem
- 2.1-8.4.2.5 Heated Potable Water Distribution Systems:
 (2) ☐ heated potable water distribution systems serving patient care areas are under constant recirculation
☐ non-recirculated fixture branch piping max. length 25'-0"
- (3)(a) ☐ no installation of dead-end piping (except for empty risers mains & branches for future use)
 (3)(c) ☐ any existing dead-end piping is removed
☐ check if not included in project
- (4)(a) ☐ water-heating system supplies water at temperatures & amounts indicated in Table 2.1-4
- 2.1-8.4.2.6 Drainage Systems:
 (1)(a) ☐ drainage piping installed above ceiling of or exposed in electronic data processing areas & electric closets have special provisions to protect space below from leakage & condensation

- (1)(b) ☐ drip pan for drainage piping above ceiling of sensitive area
☐ check if not included in project
☐ accessible
☐ overflow drain with outlet located in normally occupied area

2.1-8.4.3 PLUMBING FIXTURES

- 2.1-8.4.3.1(1) ☐ Materials used for plumbing fixtures are non-absorptive & acid-resistant
- 2.1-8.4.3.2 Handwashing Station Sinks:
 (1) ☐ handwashing sinks designed with basins that will reduce risk of splashing to areas where medications are prepared
 (2) ☐ sink basins have nominal size of no less than 144 square inches
☐ sink basins have min. dimension 9 inches in width or length
 (3) ☐ sink basins are made of porcelain, stainless steel or solid-surface materials
 (5) ☐ water discharge point min. 10" above bottom of basin
 (7) ☐ anchored so that allowable stresses are not exceeded where vertical or horizontal force of 250 lbs. is applied
 (8) ☐ sinks used by staff have fittings that can be operated without using hands (may be single-lever or wrist blade devices)
- (a) ☐ blade handles
☐ check if not included in project
☐ at least 4 inches in length
☐ provide clearance required for operation
- (b) ☐ sensor-regulated water fixtures
☐ check if not included in project
☐ meet user need for temperature & length of time water flows
☐ designed to function at all times and during loss of normal power

2.1-8.6.2 ELECTRONIC SURVEILLANCE SYSTEMS

- ☐ check if not included in project
- 2.1-8.6.2.2 ☐ monitoring devices are located so they are not readily observable by general public or patients
- 2.1-8.6.2.3 ☐ electronic surveillance systems receive power from essential electrical system