


# *Relative Risk of Virus Contamination from a WTP can now be Accurately Assessed for Adjacent Growing Areas.*



## *Combining Final Effluent MSC Analyses with Dye Study Results*

Thomas Howell, Spinney Creek Shellfish, Inc. Eliot, ME  
NESSA April 9, 2019

Final Effluent MSC  
Analyses with Dye  
Study Result



Optimized Estimation  
of Relative Risk of  
Viral Contamination

**Example - Relative MSC level** at the 1000:1 dilution line

Typical Levels Expected = Geomean of MSC in Final Effluent/1000

Highest Levels Expected = P95 of MSC in Final Effluent/1000

This normalizing procedure can be used to better assess the relative public-health risk from viruses originating from a particular WTP.

Once normalized and expressed as the MSC concentration at particular locations in the growing area, one can assess the impact on the Growing Area on a relative basis.

“1,000:1” is simply an educated guess,  
a negotiated default.

When discussing prohibited areas and dilution zones, the most important factor is **final effluent quality** which can vary from <1 to >100,000 PFU/100ml, a factor of 5 logs.

In the far-field zone (generally greater than 300:1), dilution approaches a linear relationship with distance from the outfall.

Final Effluent Quality more important than a particular Dilution Line.

If you really want to know the risk, look at the stats of a time series of MSC from final effluent samples.

# Interpretation Matrix for Final Effluent MSC Time-series Analyses

Effluent Quality at Outfall	MSC Levels PFU/100ml	Minimum Dilution Required	Est. Max MSC at Min. Dilution	Recommended Max P95 <sup>(3)</sup>
Untreated Sewage	$\pm 230,000$ <sup>(2)</sup>	100,000:1 <sup>(1)</sup>	2.3 PFU/100ml	
Partially Treated	<50,000	100,000:1	0.5 PFU/100ml	50,000
Secondary Effluent	<5,000	10,000:1	0.5 PFU/100ml	5,000
Chlorinated Effluent	<500	1,000:1 <sup>(4)</sup>	0.5 PFU/100ml	500
UV-disinfected Effluent	<50	300:1 <sup>(5)</sup>	0.16 PFU/100ml	50

(1) NSSP recommends dilution from 1,400,000 FC/100ml to 14 FC/100ml from a source of untreated sewage to the approved growing area. This represents a dilution of 100,000:1 based on the FC standard.


(2) Estimated average of MSC level in sewage from influent data.

(3) P95 calculated from 45 final effluent samples collected biweekly or preferable tri-weekly.


(4) 1,000:1 from NSSP Guidance

(5) 300:1 RMZ from Guidance


## Hampton, NH (secondary plus chlorination) 4/1/19




## Newmarket, NH (secondary plus chlorination) 4/1/19




## Dover, NH (tertiary treatment UV) 4/1/19




## Greenwich, CT (Advanced with UV) 4/1/19



## Durham, NH (Secondary Chlorination) 5/1/18



## Mystic, CT (Secondary Bio-mag UV) 5/1/18



Effluent Quality at Outfall	MSC Levels PFU/100ml	Minimum Dilution Required	Est. Max MSC at Min. Dilution	Recommended Max P95 <sup>(3)</sup>
Untreated Sewage	±230,000	100,000:1	2.3 PFU/100ml	
Partially Treated	<50,000	100,000:1	0.5 PFU/100ml	50,000
Secondary Effluent	<5,000	10,000:1	0.5 PFU/100ml	5,000
Chlorinated Effluent	<500	1,000:1	0.5 PFU/100ml	500
UV-disinfected Effluent	<50	300:1	0.16 PFU/100ml	50

WTP Facility	Geomean	P95	Recommendation	Max MSC
Hampton, NH	2	17	300:1	0.05
Newmarket, NH	88	107	1000:1 0.11	
Dover, NH	2	20	300:1	0.07
Greenwich, CT	2	11	300:1	0.04
Durham, NH	15	326	1000:1 0.33	
Mystic, CT	1	8	300:1	0.03

# Considerations of the Time-series Analysis Approach for the Assessment of **Final Effluent** Samples

- Only final effluent released under “normal operating conditions” is impactful on adjacent growing areas in a predictable way.
- Combining the results of dye studies with final effluent assessments gives the best estimate of **MSC concentration at any given dilution line**.
- Using the P95 value from the assessment database gives an upper limit to variation under normal operating conditions
- Estimated maximum MSC at a minimum dilution line gives an independent estimate of **relative viral risk** from the evaluated WTP.
- Final Effluent Assessments are more meaningful for classification purposes than shellfish meat assessments which can be challenging to interpret.
- Approach more consistent with NSSP evaluation of growing area W/Q

# Benefits of the Time Series Analysis Approach for the Assessment of **Pre-treatment Effluent** Samples

- Yields important insight into the viral performance of the WTP before the final step of disinfection.
- Helps to understand the challenge presented to the disinfection system
- Log Reduction Values (LRVs) can be readily calculated for the disinfection process (less meaningful with indeterminates)
- Turbidity is easily measured in the laboratory and at times can impact the LRVs and final effluent quality.
- Running the single pre-treatment is adequate for this purpose.
- **Sampling Influent is not recommended**; hazardous, unpleasant often in confined spaces, variable by nature, and un-needed.

**Project Partners** - Work Funded by NOAA and Sea Grant via New  
Hampshire Sea Grant Program  
Cooperative Agreement No. NA14OAR4170083

Dr. Steve Jones, Research Professor, UNH  
Project Leader, Overall Project Mngt.

Tom Howell, SCS, Co-Project Leader,  
NSSP-conforming MSC Laboratory

Dr. Kevin Calci, Captain, FDA, Co-Project  
Leader, Method Developer, Gulf  
Coast Shellfish Laboratory (GCSL)

Greg Goblick, P.E., FDA CFSAN  
Co-Project Leader, Hydraulic Dye  
Studies and Modeling

Kristen DeRosia-Banick, CT DOA/BOA  
Co-Project Leader, Mystic River, CT  
Case Study Manager.

Chris Nash, NH DEP, Project Partner,  
Great Bay Estuary, NH, Case Study Mngr.

Tessa Getchis, CT Sea Grant Extension,  
Project Partner, Outreach

Lori Howell, SCS, ISSC Executive Board  
Member, Project Partner, Administrative  
and Laboratory Assistance