

Family Child Care Licensing

TECHNICAL ASSISTANCE: Protection from Window Hazards

606 CMR 7.07(10)(h) requires that children be protected from the hazards presented by windows, such as falling through an open window; injuries caused by a loose-fitting window; and broken glass from falling against and breaking a window installed close to the floor.

In addition to exercising good judgment and proper supervision, providers must take protective measures to prevent these injuries, which may include:

- Opening windows in child care spaces only from the top, so that the open area is at the top, not the bottom, of the window;
- Ensuring that furniture is placed far enough from an open window to prevent a child from climbing to reach the opening;
- Ensuring that furniture or other natural barriers prevent children from falling directly against closed, low-mounted windows;
- Installing or using blocking devices which prevent a window opened from the bottom from being raised more than four inches;
- Using blocking devices to ensure that casement windows (that crank-out) are opened no more than 4 inches;
- Installing window guards or barriers on open windows or on any low-mounted windows in child care space that are not otherwise protected¹.

Secure screens may only be used to prevent children from falling out of open windows that are <u>less than four feet from ground level</u>. Windows that have been approved as emergency evacuation exits may not be protected by window guards or barriers that would prevent immediate exit from the window.

¹ Care should be taken to ensure that window guards and barriers will not prevent access by fire safety personnel in the event of an emergency.