Neighborhood Traffic Circles on Pearl St – Somerville, MA

Site and Treatment Description

Since 2020, Somerville has applied at least 19 traffic calming treatments in the neighborhood bounded by McGrath Highway, Broadway, the city line, and Washington Street, with the primary motivation being Safe Routes to School. Among the treatments are three neighborhood traffic circles installed in 2023 at Pearl St @ Glen St, Pearl St @ Myrtle St, and Oliver St @ Glen St. This treatment was chosen to reinforce the existing allway Stops at these intersections and thus make it safer for children to cross.



Pearl is classified as a collector street (ADT = 2250) while Glen (ADT = 1550) and Myrtle (ADT = 2350) are locals. The neighborhood traffic circles are small circles (diameter \approx 12 ft) with concrete curbs between 5 and 7.5 inches high. Two have plantings in the middle, while the third cannot have plantings because it has a manhole cover. They are not roundabouts or mini-roundabouts, nor are they signed as a "traffic circle" or "rotary." This means that larger vehicles turning left such as school buses are allowed to turn left in front of the circle (tracking almost the same as they would if there were no circle). All approaches have Stop signs (as they did before).



Neighborhood Traffic Circle at the Intersection of Glen Street and Oliver Street, Somerville

Before-after Speed Results

Because there were Stop signs on every approach before as well as after, the circles were not intended to reduce general traffic speed, but as a proactive measure to improve pedestrian safety and comfort by preventing violations from driving through the Stop sign at speed, and thus making crossing pedestrians (especially children) certain that approaching vehicles will be stopping or at least slowing to pedestrian speed.

Design Specs and Cost

Tetra Tech, a consultant, designed the neighborhood traffic circles. Detailed construction design plans are provided in Appendix A. The diameter of the outer apron of the traffic circles is 12 ft, with an inner raised circle with 6 ft diameter. The outer apron is 1.5 inches high (one inch beveled curb reveal, and paved with cobble a half-inch higher) and is mountable. The inner circle has a curb that is 16 inches above street level.

Before construction, City staff marked off each circle with cones and paint and had the fire department test it to ensure they could pass. After construction, while the design had provided more than the 12 ft clearance between the corner curbs and inner circle curb requested by the DPW, the DPW realized they actually needed 17 ft between curbs to accommodate their larger snowplows. The contractor rebuilt the inner circle's curbs accordingly, shifting their center so that the inner circle is no longer centered in the apron. This experience has informed the spec which the City intends to apply in the future.

Construction cost per traffic circle was roughly \$6,000.

Support Story

From the mayor and City Council, there is a strong commitment to Vision Zero and to Safe Routes to School. While emergency response and DPW staff were skeptical at first, they worked cooperatively with the City's Department of Transportation and Infrastructure to find a design that would meet the project objectives while still providing adequate space for fire and snow-clearance vehicles.

There was some citizen opposition and negative press, but most of the public has been supportive, as well as the mayor and City Council. The Department of Transportation and Infrastructure doesn't take public support for granted, but works hard to earn it by providing information to residents and by being transparent with traffic calming project plans and evaluations through their web site. In recent City Council elections, candidates supporting Safe Streets policies outpolled those against the policies by a margin of 4 to 1.

Maintenance Tips

Additional investigations should be conducted to ensure that largest road users, including fire vehicles, can move around the traffic circle. Greenery implementation in the center of islands should not overlap with any major utility construction. Additionally, reflective signage on the island is highly recommended.

Other Lessons

Working cooperatively with fire and DPW was critical. At the same time, it was equally vital for fire and DPW to embrace the City's traffic calming goals, so that it was not a question of IF the City would install speed management devices, but HOW.

Projects that involve contractors working with concrete, granite, and asphalt require more staff capacity than the City had up to 2019; before that, speed management projects were limited to "signs and lines." The City hired new staff that can manage projects and contractors, and its capacity has scaled up to a pace of about 50 devices (speed humps, curb extensions, crossing islands, and so forth) per year.

Somerville's Department of Transportation and Infrastructure has an analytics team in house that, among other things, prioritizes streets for speed management and evaluates projects. myrThey make an annual report on policy development; annual reports will be coming out in the next 2-3 months.

Future Plans

The City plans to install more neighborhood traffic circles as well as other speed management devices.

Appendix





							PROP	RALLA			100 F	BANK	EDGE		HAV to HAVE	WDDI	OUND	UNDE				CURD CURD	· PM · PM PARK	• WG • WG WATE	-SIZE & TYPE TREE	→ UPL → UPI UTU	-> ULT -		A TRAN	- 18 TOWN	NON BHM B			0 0 0 0 0 0 0 0 0 0 0		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	- C0.80. 米 LiGH.	P P P HYDR									
							PERTY LINE OR APPROXIMATE PROPERTY LINE	ROAD SIDELINE	N OR DITY LAYOUT	TEHIGHWAY LAYOUT	T DUCTOR DOUGHER	OF RIVER OR STREAM	FOF NICROMITING AND OVERLAY	OR BOTTOM OF SLOPE	BALES/SULT FENCE	D FENCE	RD RALL - STEEL POSTS RD RALL - WOOD POSTS	ERCROUND WATER MAIN (DOUBLE LINE 24 INCH AND OVER)	ERGROUND SEVER MAIN (DOUBLE LINE 24 INCH AND OVER) ERGROUND TELEPHONE DUCT (DOUBLE LINE 24 INCH AND OVER)	ERGENOUND ELECTRIC DUCT (DOUBLE LINE 24 INCH AND OVER) ERGENOUND ELECTRIC DUCT (DOUBLE LINE 24 INCH AND OVER)	TOURS (DWTHE-GROUND SURVET DATA) TOURS (PHOTOGRAMVETRIC DATA)	DNG CABLEYWAR	CING METER CING METER	BR GATE	2 U		TY POLE W/1 LIGHT	VEMISSION FOLE	JERSE OR TRIANCULATION STATION	N OR CITY BOUND	INCOUSE I IS HIGHNEY BOUND	ER MANHOLE	BHONE MANHOLE	MANHOLE	NAGE MANHOLE STRIG MANHOLE	E MANHOLE	ATY BOUND	r pit RANT	ITORING WELL	GATE COL	TRO HANDHOLE	T DRCULAR	BOX	PUMP	2H BASIN 2H DASIN CURB INLET	SEY BARRIER	
										I I									Internetional	002	و	EXISTING		DOUTHEAT MADEN] 0		F P		Ĩ	0.0	d	d E	j		BI POPULA	ţ	å I	° →	€ ⊕	õ	j c	1 [23	210]	EXISTING	TROUPING STREETS
		12. D.Y.	12" DVeL	a orus	and a		8ª FWI	AT DW	6' BYL		0, DBAT	\$"DBWL	72.87		e pu	17 SWI	8'SM		12° SL	R	و	PROPOSED	and an an over on			ſ] 0	8 9	F 1	0	¶ 1	4. n	q	þ		•	2019 2	4	ŧ	t.	- 10	1	1	D	2103	PROPOSED	
		12' DOTTED VELLOW LINE (3' LINE - 8' GAP)	 2" DOTTED WHITE LINE (3" LINE - 9" GAP) 	 S" DOTTED YELLOW UNE EXTENSION (2" LINE, 8" GAP) 	 OTTED WHITE LINE EXTENSION (2 LINE, © GAP) 	6" DOTTED YELLOW UNE	e dotted white une			6" BROKEN WHITE LINE	6" DOUBLE YELLOW UNE	6" DOUBLE WHITE LINE	12' SOLID YELLOW LINE	- 6" SOUD YELLOW UNE	12" SOLID WHITE LINE	0" SOLID VAHILE LINE		CRCSSWALK	12' STOP LINE	LEGEND "ONLY" - WHITE	PAVENENT ARROW - WHITE	DESCRIPTION				TEATTIC COMMINSTRATIC (OR AS NOTED)	PULL BOX 12"A12" (OR AS NOTED)	LOAD CENTER ASSEMBLY	CONTROL CABINET, POLE MOUNTED	CONTROL CABINET, GROUND WOUNTED	MAST ARM WITH LUWINAIRE OPTICAL PRE-EMPTION DETECTOR	DILLBOARD	SICN AND POST (2 POSTS)	HIGH MAST POLE OR TOWER SIGN AND POST	MAST ARM, SHAFT AND BASE (ARM LENGTH AS NOTED)	SIGNAL POST AND BASE (ALPHA-RUIVERIC DESIGNATION NOTED)	PEDEST RIAN STONAL HEAD, (TYPE AS NOTED OR AS SPECIFIED) RATI ROAD STONAL	FLASHING BEACON	VEHICULAR SIGNAL HEAD, OPTICALLY PROGRAMMED	EMERCENCY PREEMPTION CONFIRMATION STROBE LIGHT	PEDESI KIMI POSH DO LLON, SIGN (DIREC LLONAL ARKAWANS SHOWN) AND SADDLE	MICROWAVE DETECTOR	VINE OVER DETECTION (A XO THE ONLEGS OTHERWARE STEVINED) VIDEO DETECTION CAMERA		TRAFFIC SIGNAL HEAD (SIZE AS NOTED)	DESCRIPTION CONTROLLER PHASE ACTUATED	
	PSB PSB	202	POT	900	PCC	88	NIC	NH0	MB	NAX	55	6-	JOT	HOR	-MAA	GRD	GRAN	e e e	9 g	883	FLDSTN	F80	EXC EXC	EOP EXIST (or E)	EMB CLEV (or CL	DWY	99	CHV	DOR	CONST CR GR	CONC	8 8	CMP	p 6	មិ ច	CEM S	88	8	1 803	88	81.DC	<u>8</u> 8	ACCM PIPE BIT.	ALC:	AD-1	AADT	
	PROPOSED PLANTABLE SOL BORROW POINT OF TANGENCY	PROJECT	POINT ON TANGENT	POINT OF INTERSECTION POINT ON DURVE	POINT OF COMPOUND CURVATURE PROFILE GRADE LINE	NUMBER POINT OF CURVATURE	MINIMUM NOT IN CONTRACT	MANHOLE MASSACHUSETTS HIGHWAY BOUND	MALBOX	LEFT	LIGHT POLE	LENGTH OF CURVE LEACH BASIN	JUNCTION	HORIZONTAL HYDRANT	HOT MIX ASPHALT	GUARD	GRANITE	GUTTER INLET WITH OURB INLET GALVANIZED IRON PIPE	GAS GATE GUTTER INLET	GARAGE GROUND	FILLOSTONE	FRAME AND GRATE	EXCAVATION FRAME AND COVER	EDGE OF PAVEMENT	ENDANGMENT	STEADY DON'T WALK - PORTLAND ORANGE DRIVEWAY	DIAMETER DUCTILE IRON PIPE	DES GN HOURLY VOLUME DROP NUET	DEPARTMENT OF CONSERVATION & RECREATION	CONSTRUCTION CROVALGRADE	CONCRETE	CORRUGATED STEEL PIPE COUNTY	CORRUGATED METAL PIPE CORRUGATED PLASTIC PIPE	CHAIN LINK FENCE CENTERLINE	CAST IRON PIPE	CEMENT CONVENTIE IN PROVINT 1	CEMENT CONCRETE	CATCH BASIN	BOTTOM OF SLOPE	BENCHMARK BY OTHERS	BULDING	BOTTOM OF CURB BOUND	ASPHALT COATED CORRUGATED METAL P BITUMINOUS	APPROXIMATE ASPHALT CONCRETE	ADJUST	ANNUAL AVERAGE DAILY TRAFFIC	na we
			¥.	< >	TR SIG TBC	죽 주	R	ę و	9V ABN	282 180	e B B	C PR	22	퀽권	R	DW	CAB	TPAFFIC SL	WM X-SECT	WIP NO.	500	VAR	두긥	TC S	TAN	T 8V	SHLO	STA	SMH	SP RT	R&R	RR	RET WALL	REM	B	RAD	P/5/W	22	Pvc	GENERAL	ABBREVIAT		PE				
Per Manauns - This, ethories a devergi			STEADY YELLOW LEFT ARROW	STEADY WALKING PERSON STEADY CIRCULAR YELLOW	TRAFFIC SIGNAL TRAFFIC SIGNAL CONDUIT	STEADY RED LEFT ARROW STEADY RED RIGHT ARROW	PAN, TILT. ZOOM STEADY CIRCULAR RED	PEDESTRIAN	STEADY GREEN VERTICAL ARROW	STEADY OREEN SLASH LEFT ARROW	STEADY GREEN LEFT ARROW STEADY GREEN RIGHT ARROW	FLASHING VELLOW RIGHT ARROW STEADY DIRCULAR OREEN	FLASHING CIRCULAR YELLOW FLASHING YELLOW LEFT ARROW	FLASHING RED LIFFT ARROW FLASHING RED RIGHT ARROW	FLASHING DIRGULAR RED	STEADY UPRAISED HAND	CABINET	TON & LARRED FURTHING	CROSS SECTION	WATER GATE WROUGHT IRON PIPE	VERTICAL CURVE	VARIES	UTUTY POLE	TOP OF CURB TOP OF SLOPE	TEMPORARY	SIDEWALK TANCENT DISTANCE OF CURVETRUCK %	STORYING SIGHT DISTANCE STATE HIGHWAY LAYOUT LINE	STATION	SHOULDER SEWER MANHOLE	STONE BOUND	REMOVE AND RESET REMOVE AND STACK	RALROAD	RETAINING WALL	REMOVE	ROAD	REMOVE AND DISPOSE	PAVED WATER WAY	POINT OF VERTICAL TANGENCY	POINT OF VERTICAL CURVATURE		TIONS (cont.)						
at to yoste	4 0-21	ONG EP	CHARL THE	FRO: 1433141772				(Pearl Son Leg	Stre Stre nervil jend	ofSo etane lie, M and A	d Sek assac Abbre	ville ect Are chuse t	ang N S				0	0471 545/22	FIRS	R FT CA	rissk	2N				EP														(T	E	TE	TR	A 7	TEC tataka tkawan	CH Real



analazi tay termi ing terleti kutok bir tay digin galari ku kubakasi ingeri ingeri kukura juli k

