



NOTES:

1. THE INTERIOR OF ALL BOX GIRDERS, INCLUDING ALL STRUCTURAL STEEL COMPONENTS WITHIN EACH BOX GIRDER (SUCH AS DIAPHRAGMS, CROSS-FRAMES, CONNECTION PLATES, ETC.) SHALL BE PAINTED GLOSS WHITE (FEDERAL STANDARD 595B, COLOR NO. 17925).
- 2a. ZERO DISTANCE REFERENCE LINE LOCATED AT WEST CENTERLINE OF BEARING. *(for bridges with East and West abutments)*
- 2b. ZERO DISTANCE REFERENCE LINE LOCATED AT SOUTH CENTERLINE OF BEARING. *(for bridges with North and South abutments)*
3. INDICATE DISTANCES SEQUENTIALLY AT FIVE (5) FOOT INTERVALS WITHOUT INTERRUPTION FULL LENGTH WITHIN EACH BOX GIRDER WITH BLACK LINES AND NUMERALS ON LEFT WEB.
4. DO NOT CARRY OVER THE MEASURED DISTANCE SEQUENCE BETWEEN SEPARATE BOX GIRDERS WITHIN THE SAME GIRDER LINE OVER PIER(S).

INTERIOR PAINTING REQUIREMENTS

SCALE: $\frac{3}{4}" = 1'-0"$



LRFD BRIDGE
MANUAL, PART II

INTERIOR PAINTING REQUIREMENTS STEEL BOX GIRDERS

DATE OF ISSUE
JUNE 2013

DRAWING NUMBER

5.3.16